



Speaker 50W

MS-50BT

Features

- Versatile and Unobtrusive Speaker Designed for a Variety of Applications
- Electronic Overload Circuit to Protect Tweeter
- Rated Output: 20W
- 4Ω or 70V Impedance
- Two-Way Speaker: 2 1/4" Dome Tweeter and 5" Cone Woofer
- Frequency Response: 120Hz - 20kHz
- Color Coded Push-Type Connection Terminals
- Compatible with Optional FSB-1 Bracket



Description

The MS-50BT is a versatile and unobtrusive music system speaker that is designed for a variety of applications. The speaker contains a separate dome tweeter and cone woofer. An electronic circuit is provided to protect the tweeter from overload. Power handling is rated at 20W and impedance is rated at 4Ω or 70V. The speaker incorporates color-coded connection terminals, red (positive) and black (negative), providing simple identification. The MS-50BT connection terminals are push-type, allowing easy cable connection. An optional mounting bracket (FSB-1) is available for wall or ceiling installation and provides directional adjustment.

Technical Specifications

ELECTRICAL	MS-50BT
Rated Input	20W/4Ω or 20W/70V Speaker Line
Frequency Response	120Hz - 20kHz
SPL (1W/1m)	90dB
GENERAL	
Color	Black
Weight	8.6lbs.
	3.2kg
Dimensions (W x H x D)	5.9" x 9.4" x 5.9"
	150mm x 240mm x 150mm
Bracket (Optional)	FSB-1