

ATTENUATORS AND PROGRAM SELECTOR

CV-4 / CV-40 / CV-P



The CV-4 and CV-40 volume controls models have been designed to work on 100 V inputs and outputs lines, with a regulation of 6 steps by means of a 12 positions endless switch. In order to facilitate the volume control, a “zero” has been inserted between every two levels.

They are provided with a surety paging connection that allows to send the messages even though the volume control switch is off. The messages will be sent at the maximum volume. The surety paging can be done simultaneously with the priority paging over the music channel.

They are available in four colours: Ivory, White, Silver and Black.

The CV-P program selector uses a 12 positions endless switch for the program selection, so that, if the position “6” is exceeded, the program selection starts again from 1 to 6.

It is provided with a surety paging facility that connects the Program 1 to the speakers bypassing the selector.

It is also available in four colours: Ivory, White, Silver and Black.

These 3 models can be optionally supplied with colour frames.



SPECIFICATIONS

	CV-4	CV-40	CV-P
Power supply		24 V.d.c.	
Input	100 V line		6 x 100 V line
Output		100 V line	
Regulated power	Up to 4 W	Up to 40 W	-
Flush-mounting box		Included, model L170	
Consumption		10 mA	
Dimensions (mm)		45 x 45	
Volume control	Regulated by steps (6)		-
Finishing		In Ivory, White, Silver or Black colour	
Remarks	Color frames (optional): Ivory (model M420I), Silver (model M420S), White (model M420W) and Black (model M420B)		

