

# 10-6-3W-sphere-loudspeaker **KM-180T/EN5424** in full-metal-design



**KM**  
**180**  
**EN 5424**  
**10W**  
**6W**  
**3W**

**S P H E R E L O U D S P E A K E R**

- APPLICABLE AS **6W & 10W-VERSION**
- FULL-METAL-DESIGN
- FIRE-RESISTANT & LOW FLAMMABILITY
- BRUSHED **STAINLESS-STEEL** LOOK AVAILABLE
- **50-HZ-STABLE** TRANSFORMER
- OPTIONAL **CERAMIC-CLAMP** & **THERMO-FUSE** AVAILABLE
- 360° SOUND-RADIATION UP TO 1 KHZ

- **KM-180T/EN-5424-CERTIFICATED-VERSION:  
ORDER-NUMBER:**

**KM-180T/EN-5424**  
CPD-NR: 1293-CPD-0272

## TECHNICAL DATA:

## KM-180T/EN5424

Loudspeaker:	10/15W Broadband w. HF-Conus
Power Consumption:	100V-10-6-3W
Frequency-Range:	120-16 000 Hz
EN-Sensitivity 1W/4M:	78,0 dB
SPL max 10W/4M:	89,30 dB
SPL 1W/1M max. EASE/Ulysses:	92 / 93 dB (3,5 / 7,5 KHz)
SPL 10W/1M max. EASE/Ulysses:	102 / 103 dB (3,5 / 7,5 KHz)
Radiation H (0,5/1/2/4kHz):	360°/360°/70°/52°
Radiation V (0,5/1/2/4kHz):	360°/360°/70°/52°
Dimensions (dia):	180 mm
Weight:	1,7 Kg
Colour:	white, opt. brushed-stainless-steel-look

