

ARRI
COMPACT



COMPACT DAYLIGHT

Using single-ended lamp technology to achieve size and weight reductions of up to 75% over the nearest competitors, the ARRI Daylight Compact range now includes 125W, 200W, 575W, 1200W, 2500W, 4000W, and 6000W versions.

For extra convenience the smaller 125W and 200W units are supplied as kits complete with mains powered dimmable electronic ballast, 4-leaf barndoor, diffuser frame, & cable in sturdy aluminium carry cases. For greater flexibility, these smaller units can also be used with ARRI's electronic 125W / 200W battery ballast.

ARRI Compacts use carefully optimised short focal length lenses, giving ultra smooth performance at very high output levels, over the widest beam angle range. All units can be dimmed down to 50% brightness, with no significant colour temperature shift.

Additional features, such as fully motorised remote control, pole operation, or remote dimming via DMX 512 ballast variants or analogue louvre shutters, are all available as options.

Modular construction throughout the range means that many COMPACT accessories and components are also used on other ARRI products, such as the STUDIO and JUNIOR ranges, allowing greater efficiency with operational and maintenance costs.

ARRI's elegant modular construction, using aluminium extrusions and lightweight pressure die-castings, offers great structural strength, while being light and weather resistant. All serviceable parts are readily accessible, and all ARRI fixtures naturally comply with the latest European safety standards.

- Single Ended technology for size & weight reductions.
- 125W, 200W, 575W, 1.2kW, 2.5kW, 4kW, 6kW versions.
- Short focal length lenses ensure output over a wide range of beam angles is unrivalled.
- Dimmable to 50% with no significant colour temperature shift.
- Corrosion-resistant aluminium construction for outside use.
- Easy service access.
- 125/200W and 575/1.2 Electronic Battery Ballasts.



ARRI Compact 6000W


Manual Lamphead, complete with 4-leaf Barndoor, Diffuser Frame and Wire Guard L0.75700.SB

Size (mm): 660H x 600W x 550L
Weight (kg): 29
Lens Size (mm): 420

ARRI Compact 6000T

Theatre version head only L1.75710.B

Size (mm): 660H x 600W x 550L
Weight (kg): 30




4-leaf Barndoor L2.82150.0



Diffuser Frame L2.82155.0



Scrim Set L9.82160.M



ARRI Wind Up Stand LS.387.S



Conventional Ballast 6000W L2.75841.0



Electronic Ballast 6000W L2.76171.0



7m Head to Ballast Cable L2.75710.0L

15m Head to Ballast Cable L2.75710.AL



COMPACT DAYLIGHT



ARRI Compact 4000W

Manual Lamphead, complete
with 4-leaf Barndoor,
Diffuser Frame and
Wire Guard L0.74000.SB


Size (mm): 538H x 537W x 425L
Weight (kg): 20
Lens Size (mm): 300

ARRI Compact 4000T

Theatre version head only L1.74010.B

Size (mm): 538H x 537W x 425L
Weight (kg): 21

Light Output (lux)*



4-leaf Barndoor
L2.81200.0




8-leaf Barndoor
L2.81210.0



Diffuser Frame
L2.81220.0



Scrim Set
L9.81230.M



Snoot
L2.81225.0



Stand
LS.087



Conventional Ballast
4000W



L2.75839.0
Electronic Ballast
EB 2500/4000W
L2.76640.0
EB 575-4000W
L2.76671.0



7m Head to Ballast Cable
L2.75620.0L
15m Head to Ballast Cable
L2.75620.CL



ARRI Compact 2500W

Manual Lamphead, complete
with 4-leaf Barndoor,
Diffuser Frame and
Wire Guard L0.73670.SB


Size (mm): 520H x 480W x 360L
Weight (kg): 15
Lens Size (mm): 250

ARRI Compact 2500T

Theatre version head only L1.73680.B

Size (mm): 520H x 480W x 360L
Weight (kg): 15.5

Light Output (lux)*



4-leaf Barndoor
L2.80950.0



8-leaf Barndoor
L2.80960.0



Diffuser Frame
L2.80970.0



Scrim Set
L9.80980.M



Snoot
L2.80975.0



Stand
LS.6



Conventional Ballast
2500W



L2.75014.E
Electronic Ballast
EB 2500W
L2.76635.0
EB 2500/4000W
L2.76640.0



7m Head to Ballast Cable
L2.75620.0L
15m Head to Ballast Cable
L2.75620.CL



ARRI Compact 1200W

Manual Lamphead, complete
with 4-leaf Barndoor,
Diffuser Frame and
Wire Guard L0.73770.SB


Size (mm): 440H x 340W x 295L
Weight (kg): 9
Lens Size (mm): 175

ARRI Compact 1200T

Theatre version head only L1.73735.B

Size (mm): 440H x 340W x 295L
Weight (kg): 9.5

Light Output (lux)*



4-leaf Barndoor
L2.79870.0




8-leaf Barndoor
L2.79900.0



Diffuser Frame
L2.79890.0



Scrim Set
L9.79860.M



Snoot
L2.79880.0



Stand
LS.5



Conventional Ballast
1200W



L2.75012.E
Electronic Ballast
EB 575/1200W
L2.76125.0



Universal Electronic Ballast 575-4000W
L2.76671.0
Universal AC/DC Ballast 575/1200W
L2.76230.0

7m Head to Ballast Cable
L2.75600.0L
15m Head to Ballast Cable
L2.75600.CL




ARRI Compact 575W

Manual Lamphead, complete
with 4-leaf Barndoor,
Diffuser Frame and
Wire Guard L0.73770.SB

Size (mm): 340H x 290W x 240L
Weight (kg): 7.5
Lens Size (mm): 130

Light Output (lux)*



4-leaf Barndoor
L2.79670.0



8-leaf Barndoor
L2.79700.0



Diffuser Frame
L2.79690.0



Scrim Set
L9.79660.M



Snoot
L2.79680.0



Stand
LS.4



Conventional Ballast
575W



L2.75010.E
Electronic Ballast
EB 575/1200W
L2.76125.0



Universal Electronic Ballast 575-4000W
L2.76671.0
Universal AC/DC Ballast 575/1200W
L2.76230.0

7m Head to Ballast Cable
L2.75600.0L
15m Head to Ballast Cable
L2.75600.CL



COMPACT DAYLIGHT

THEATRE COMPACT SERIES

The revolutionary THEATRE COMPACT series has developed in special recognition of the unique requirements of Theatre lighting professionals and is now available in 1200 - 6000W versions.

All models are available with special ballast variations from conventional ballasts with remote on/off to electronic ballasts with remote dimming and ignition by DMX 512 control protocol.

The Theatre Compacts combine all the advantages of power and smooth beam characteristics offered by the standard Compacts but have additional features.

All units are supplied with low profile graphite coloured body shells and strengthened stirrups with convenient grab handles for fast, low profile, overhead rigging. Centre balance can be easily adjusted to allow for front loading of scrollers or louvres.

Each unit is fitted as standard with leak-proof square section door frames designed to accept colour scrollers and/or louvre shutters as well as 4 or 8 leaf barndoors.

Glass dichroic mirrors are used in place of aluminium reflectors to transmit infra red radiation through the rear of the lamphead, ensuring that heat transfer through scrollers and louvres is kept to a minimum.


- Same benefits & performance as standard Compacts.
- Adjustable centre of balance.
- Light spill resistant door baffles.
- Riggers grab handles and reinforced stirrups.
- Glass dichroic mirrors to divert heat from scrollers.
- Door frames accept scrollers and louvres.
- DMX or analogue control via conventional or electronic ballast variants to special order.



ARRI Compact 200W

Manual Lamphead, complete with 4-leaf Barndoor, Diffuser Frame, Electronic Ballast, 7m cable and transport case L0.73330.X

Size (mm): 290H x 200W x 180L
Weight (kg): 3
Lens Size (mm): 112




4-leaf Barndoor
L2.79470.0



Diffuser Frame
L2.79490.0



Scrim Set
L9.79460.M



Snoot
L2.79480.0



Heavy Duty Baby Stand
LA.4010.B



Electronic Ballast 200W
L2.76105.0



Electronic Battery Ballast
200/125W
L2.76040.B




7m Head to Ballast Cable
L2.73372.0



ARRI Compact 125W

Manual Lamphead, complete with 4-leaf Barndoor, Diffuser Frame, Electronic Ballast, 7m cable and transport case L0.71350.B

Size (mm): 230H x 190W x 170L
Weight (kg): 1.8
Lens Size (mm): 80




4-leaf Barndoor
L2.79170.0



Diffuser Frame
L2.79190.0



Scrim Set
L9.79160.M



Snoot
L2.79180.0



Large Kit Stand
LS.3



Electronic Ballast 125W
L2.76012.0



Electronic Battery Ballast
200/125W
L2.76040.B



7m Head to Ballast Cable
L2.73382.0



*1000 lux gives correct exposure for 200ASA film with aperture f4 at 24fps

In order to maintain the highest possible standards, ARRI (GB) Ltd reserves the right to alter specifications without notice