
DIGITAL DELAY DD400



Thank you for showing your confidence in us by choosing the BEHRINGER DIGITAL DELAY DD400. This ultimate effects pedal is designed to deliver 24-bit high-resolution stereo delay sounds comparable to state-of-the-art studio processors. Thanks to its parameter controls and built-intap tempo feature, you'll have plenty of cool sounds at your disposal to handle every situation.

The delay effect creates a delay of the input signal with various repetitions. Different tempo settings allow interesting delay effects.



- 1 The LEVEL control adjusts the output level.
- 2 The FEEDBACK (Feedback) control adjusts the amount of signal repetitions.
- The TIME (Delay Time) control adjusts the exact delay time. Depending on the MODE control position you can adjust it around 200 ms, 500 ms or 1300 ms. The delay time describes how fast the signal repetitions will follow after the original signal.
- [4] With the MODE control you can chose between three different delay time ranges around 200 ms, 500 ms or 1300 ms with either mono (M) or stereo (S) delay. The exact delay time can be adjusted by the TIME control. In position HOLD the signal will be repeated constantly.
- The ON/BATT LED illuminates when the effect is activated. It also serves as a battery level indicator.
- Use the footswitch to activate/deactivate the effect. The built-in tap tempo feature is also accessed through this switch.
 - Hold the footswitch down for at least one second and release to enter tap mode. The LED will blink in rhythm with the current tempo.
 - Tap the footswitch to the desired tempo. The pedal will measure the time between the last two taps and automatically employ this as the delay time. The LED will now flash in rhythm with the new tempo.
 - After a few seconds, the unit will automatically exit tap mode and the footswitch can be used to activate/deactivate the effect again.
 - Turning the Time knob will override the tapped tempo and the delay will be determined by the settings of the Mode and Time knobs.
- 7 Use this ¼" TS IN connector to plug in the instrument cable.
- The two ½" TS connectors OUT A and OUT B send the signal to your amp. Use both connectors if you want to achieve full stereo delay effect. For mono use just plug in OUT A.

Use the DC IN connection at the front of the unit to plug in a 9 V power supply (not included).

DIGITAL DELAY DD400



The BATTERY COMPARTMENT is located underneath the pedal cover. To install or replace the 9 V battery, press the hinges with a ballpen and remove the pedal cover. Be careful not to scratch the unit

The DD400 has no on/off switch. As soon as you insert the jack into the in connector, the DD400 begins running. When not using the DD400, remove the jack from the in connector. This extends the life of the battery.

The SERIAL NUMBER is located at the bottom.

2. WARRANTY

For our current warranty terms, please refer to our website at http://www.behringer.com.

3. SPECIFICATIONS

ln 1/4" TS Connector Impedance 500 kO Out A 1/4" TS Connector Impedance 1 kΩ Out B

1/4" TS Connector Impedance $1 \, k\Omega$

Power supply 9 V == , 100 mA, regulated

Behringer PSU-SB

U.S./Canada 120 V~, 60 Hz China/Korea 220 V~, 50 Hz 240 V~, 50 Hz U.K./Australia 230 V~, 50 Hz Europe 100 V~, 50 - 60 Hz Japan

Power connector 2 mm DC jack, negative center

9 V type 6LR61 Battery

Power consumption 90 mA

Dimensions (H x W x D) approx. 54 mm (2 1/8") x 70 mm (2 3/4") x 123 mm (4 4/5")

Weight approx. 0.33 kg (0.73 lbs)

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may therefore differ from those listed or shown.

4. SAFETY INSTRUCTIONS

Do not use near water, or install near heat sources. Use only authorized attachments/accessories. Do not service product yourself. Contact our qualified servicing personnel for servicing or repairs, especially when power supply cord or plug is damaged.

No utilizar cerca de agua o instalar cerca de fuentes de calor. Utilice sólo accesorios y aditamentos autorizados. No intenté reparar el producto usted mismo. Contacte a nuestro personal técnico cualificado para servicio y reparaciones, especialmente cuando la fuente o el cable de alimentación estén dañados

Не эксплуатируйте прибор вблизи от источников воды и тепла. Применяйте только авторизованные дополнительные устройства. Никогда не ремонтируйте прибор самостоятельно. Ремонт может производить только квалифицированный специализированный персонал, особенно при повреждениях сетевого провода или сетевой вилки.

水分の近くや、ヒーターなど熱気のある場所では使用しないでください。正式に認可された付属品のみを使用してください。製品はご自分では決して修理せず、特に電源コードもしくはブラグが損傷した場合には、必ず製品サービスおよびリペアの資格を有した当社の担当員にご相談ください。

不要在幕近水源的地方使用,或在靠近热源的地方安装。只使用经过许可的附件/配件。不要自己进行产品维修,**尤其是当电源线或插座损坏的时候**,请联系我们的专业服务人员有关产品维修事宜。

Die deutsche Anleitung ist erhältlich @ www.behringer.com

Manuel francophone en téléchargement sur www.behringer.com

Manual en español disponible en www.behringer.com

Manuali italiani disponibili @ www.behringer.com

Русскоязычное руководство @ www.behringer.com

Polska instrukcja dostępna jest pod adresem @ www.behringer.com

Nederlandse handleiding beschikbaar @ www.behringer.com

Suomenkielinen käyttöohje saatavilla osoitteesta www.behringer.com Svensk manual finns tillgänglig på www.behringer.com

Dansk vejledning findes på @ www.behringer.com Manual português disponível @ www.behringer.com

Ελληνικό εγχειρίδιο υπάρχει διαθέσιμο στη διεύθυνση www.behringer.com

日本語版マニュアル@ www.behringer.com

使用说明书可在 www.behringer.com 下载

Technical specifications and appearance are subject to change without notice. The information contained herein is correct at the time of printing. All trademarks (except BEHRINGER, the BEHRINGER logo and JUST LISTEN) mentioned belong to their respective owners, and such use neither constitutes a claim of the trademarks by BEHRINGER nor affiliation of the trademark owners with BEHRINGER. BEHRINGER accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary slightly from product. Our products are sold through authorized dealers only. Distributors and dealers are not agents of BEHRINGER and have absolutely no authority to bind BEHRINGEP by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER International GmbH, Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich, Germany. Tel. +49 2154 9206 0, Fax +49 2154 9206 4903