

<b>Model Name</b>	<b>PTC-150T</b>
<b>Product Name</b>	<b>HD/SD-SDI PTZ Camera (HDBaseT)</b>
<b>Video format</b>	1080p 59.94/50/29.97/25 1080i 59.94/50 720p 59.94/50 480i, 576i (on CVBS)
<b>Image Sensor</b>	1/2.8" type progressive scan CMOS sensor
<b>Effective Pixels (approx.)</b>	2.14 Mega pixels
<b>S/N Ratio</b>	50dB
<b>Min. Illumination</b>	Color: 0.4 lx B/W: 0.03 lx (F1.6, 1/30 sec, 50IRE, Gain: High)
<b>Electronic Shutter</b>	1/25 (1/30), 1/50 (1/60), 1/75(1/90), 1/100, 1/120 (1/125), 1/150(1/180), 1/215( 1/250), 1/300(1/350), 1/425(1/500), 1/600(1/725), 1/1000, 1/1250(1/1500)
<b>Zoom Ratio</b>	30x Optical Zoom
<b>Gamma Control</b>	Off / Normal / Standard Mode 1-4
<b>Iris Control</b>	Auto / Manual
<b>Digital Noise Reductions</b>	Yes
<b>On-Screen Display (OSD)</b>	English
<b>White Balance</b>	AWB / MWB / One push WB / Outdoor / Indoor / Fluorescent
<b>AGC / Gain Control</b>	Auto / Manual Max. Gain Limit
<b>Mirror / Flip Image</b>	Yes
<b>Focus Mode</b>	Auto / Manual
<b>Panning/Tilting Range</b>	Pan: 270°, Tilt: +90° to -20°
<b>Panning/Tilting Speed</b>	Manual: 1~150°/Sec Swing: 1~150°/Sec
<b>Preset</b>	50 Position
<b>Focal Length</b>	f=4.3 mm (WIDE) to 129 mm (TELE) F1.6 to F4.7
<b>Field of View (Horizontal, Wide)</b>	Approx. 63.7° (WIDE END) / 2.3° (TELE END)

<b>Image Compensation</b>	Day & Night function
<b>Video Output</b>	HDMI (V1.3) x 1 3G-SDI x 1 CVBS x 1 HDBaseT x 1 to PTC-150T Receiver Box
<b>Tally LED</b>	Dual color (Red, Green)
<b>Filter</b>	M52.0 x 0.75 Thread with UV Protection
<b>RoHS</b>	Compliant
<b>Protocol</b>	VISCA, DVIP
<b>Remote Control Interface and Transmit Distance</b>	RS-422: Transmit up to 1000m HDBaseT (RJ-45) / DVIP on Receiver Box: Transmit up to 100m
<b>F/W Update</b>	USB
<b>IR Control</b>	Yes
<b>Camera Control Unit</b>	RMC-180
<b>Accessories</b>	----
<b>Color</b>	dark blue