

6W-Wall / on-ceiling-loudspeaker DESIGN-230 / EN5424

DESIGN

230

EN
5424

WALL

—

CEILING

LOUDSPEAKER



- NEW SOFTLY-BENDED **DESIGN-CABINET**
- VERY **FAST MOUNTING** THROUGH **QUICK-SNAP-FRONT-GRILL**
- ONLY 2 DRILLING-POINTS FOR THE WHOLE LOUDSPEAKER
- HIGHLY **STABLE** ABS-CABINET V2 / HB75 OF VERY LOW **FLAMMABILITY**
- **50-HZ-STABLE** TRANSFORMER
- **TOUCH-PROTECTED** 100-V-CONNECTING-CLAMP
- WEATHER-PROTECTED & **WET-ROOM/DAMP-ROOM**-VERSIONS AVAILABLE
- OPTIONAL **CERAMIC-CLAMP** & **THERMO-FUSE** AVAILABLE

**DESIGN-EN-5424-CERTIFICATED VERSION:
ORDER-NUMBER:**

DESIGN-230/EN-5424
CPD-NR: 1293-CPD-0233

TECHNICAL DATA:

DESIGN-230/EN5424

Loudspeaker:	6W/120mm-broadband
Power-Consumption:	100V-6-3-1.5W
Frequency-Range:	80-15 000 Hz
EN-Sensitivity 1W/4M:	77,1 dB
SPL max 6W/4M:	87,0 dB
SPL 1W/1M max. EASE/Ulysses:	98,5 dB (1,3 kHz)
SPL 6W/1M max. EASE/Ulysses:	104,5 dB (1,3 kHz)
Radiation H (0,5/1/2/4kHz):	130°/105°/100°/70°
Radiation V (0,5/1/2/4kHz):	130°/115°/55°/65°
Dimensions:	230 x 170 x 80 mm
Weight:	1,2 Kg
Colour:	white

