

6W-ABS-Wall / on-ceiling-loudspeaker **WLA-230G / EN5424**

W
L
A

230G

EN
5424



W
A
L
L
-
C
E
I
L
I
N
G

L
O
U
D
S
P
E
A
K
E
R

- VERY **FAST MOUNTING** THROUGH **QUICK-SNAP-FRONT-GRILL**
- ONLY 2 DRILLING-POINTS FOR THE WHOLE LOUDSPEAKER
- HIGHLY **STABLE ABS-CABINET V2 / HB75** OF VERY LOW **FLAMMABILITY**
- **50-HZ-STABLE** TRANSFORMER
- **TOUCH-PROTECTED** 100-V-CONNECTING-CLAMP
- **WET-ROOM/DAMP-ROOM** & WEATHER-PROTECTED VERSIONS AVAILABLE
- OPTIONAL **CERAMIC-CLAMP** & **THERMO-FUSE** AVAILABLE

- **WLA-EN-5424-CERTIFICATED VERSION:
ORDER-NUMBER:**

WLA-230G/EN-5424
CPD-NR: 1293-CPD-0166

TECHNICAL DATA:

WLA-230G/EN5424

Loudspeaker:	6W/120mm-broadband
Power-Consumption:	100V-6-3-1.5W
Frequency-Range:	80-15 000 Hz
EN-Sensitivity 1W/4M:	78,00 dB
SPL max 6W/4M:	86,40 dB
SPL 1W/1M max. EASE/Ulysses:	97 dB (1,5 kHz)
SPL 6W/1M max. EASE/Ulysses:	105 dB (1,5 kHz)
Radiation H (0,5/1/2/4kHz):	180°/170°/100°/90°
Radiation V (0,5/1/2/4kHz):	180°/170°/100°/90°
Dimensions:	230 x 170 x 80 mm
Weight:	1,2 Kg
Colour:	white

