Roland



oland

2-09HR

SRECO

WAVE/MP3 RECORDER

Roland



Advanced recorders conceived and created by

Because we understand the essence of sound, we make no compromises in quality. And because we have a solid track record as a pioneer in the field, no other product family compares to the R-series' quality and ease of use. Roland WAVE/MP3 recorders symbolize a no-compromise pursuit of high-quality sound recording and a passion for perfection. Whether you choose by performance or value, you will find your solution here.

Unique ICA omnidirectional mic system accurately captures the depth and ambience of the environmen

High-quality design enables perfect and detailed recordings. The core recording component is our proprietary ICA (Isolated Capsule Architecture) omnidirectional mic system, outstanding for capturing detailed ultra-low frequencies, especially when compared to standard unidirectional mics. The shape of the special capsule that covers the unit provides focus. As a result, the sounds recorded on these recorders are realistic and have a natural stereo feel.

Floating construction reduces noise

In order to eliminate vibrations that can cause noise, the mic housing has been isolated from the unit's circuit board. It rests on a floating base enclosed in a rubber damper, providing excellent vibration insulation. These recorders achieve high-quality live recordings by reducing noise in all possible areas.



Floating construction

prevents noise from vibration

and handling (R-09HR).

Proprietary IARC analog circuitry is the key to excellent sound quality

R-Series recorders are equipped with Roland's proprietary IARC (Isolated Adaptive Recording Circuit). Input levels reaching the A/D converter are optimized to ensure that audio is digitally converted while retaining its natural, pure quality. Additionally, the independent power-supply circuitry prevents noise caused by interference between circuits. Every step has been taken to reduce noise.

imiter and AGC prevent recording errors before they happen

The Limiter and AGC (Auto Gain Control) adjust input levels to prevent recording errors. Use either of these to suit the situation, and enjoy recordings with consistent quality.



The limiter prevents distortion by compressing the level when there is excessive input from transient, high-volume sounds. With the ability to handle sources with large fluctuations in volume, these recorders are ideal for recording musical performances and vocals.



This feature amplifies weaker input and attenuates strong input to ensure a consistent overall volume. This is best for situations such as conferences where you want to capture all speakers at the same volume.

Roland, the trusted leader in music technology

Linear PCM recording exceeds audio-CD quality


With support for linear PCM recording (WAVE) up to 24-bit at 96 kHz, the R-series lets you create astonishingly realistic recordings, capturing the finest details of the source. MP3 is also supported, so you can chose the audio format that best suits your application. Recordings are captured and stored on industry-standard SDHC/SD memory cards, supporting high-quality sound and lengthy recording times.

Edit your recordings with built-in tools such as Divide and Combine

A variety of editing functions lets you customize your recorded files directly onboard on the unit. You can combine multiple files of the same format into one, for example, or divide a single file into multiple files. Regardless of the file format you recorded in — WAVE or MP3 — you can edit them right on the spot.

Divide (file splitting

Divide your file at any point after you record. You can use this in a variety of ways, including dividing a continuous file at spaces between songs.



Combine (file merging)

Combine two files. Use this to create a medley of multiple songs, for example, or merge all songs from a continuous recording into a single audio file.

Frim (trimming unwanted sections)

Keep only the parts of the recorded file that you need and erase the rest. This is an easy way for trimming out the unwanted space before and after a song. *Supported on R-05 only



WAVE/MP3 RECORDER

Stress-free usability for fast, high-quality recordings

Functions that are used most often are controllable via hardware switches, including the INPUT LEVEL button for adjusting input level, MIC GAIN for configuring mic sensitivity, and LOW CUT for eliminating irritating low-frequency noise. These compact recorders fit in your palm, and are just the right size for comfortable, single-hand operation.



Hardware switches on the back of the unit (R-09HR)

Convenient playback functions such as speed control

A variety of playback options add versatility to these recorders, including Repeat, Shuffle, and A-B Repeat.

Variable speed playback

Change the playback speed in 10 steps from 50-150% with simple button operations. This is convenient for dissecting phrases in fast-tempo songs or transcribing conference minutes.

A-B repeat

Repeat a particular section of your recording over and over. This lets you recheck a particular section of your recording over and over, and is very convenient for practicing instruments or language training.

A variety of functions to expand the range of use

- •Supports high-speed USB (USB 2.0) for fast data transfer to your computer (Windows or Mac).
- •The date and time of the recording can be stamped on the file, which makes it easier to manage your recorded data.
- Self-timer feature lets you set, in seconds, the time to begin recording.
 This is handy for recording your own performances.





Independent mic housing for accurately capturing depth of field

The R-05's internal microphone is housed in an independent enclosure that's isolated from the unit's circuit board. With its unique capsule shape, the ICA omnidirectional mic system ensures localization, and can capture the sound field accurately and realistically. The mic is enclosed in a frame made of vibration-insulating rubber material to prevent noise transmission from the unit.



Frequency Response





WAVE/MP3 RECORDER R-05

Our WAVE/MP3 recorders have become popular around the world for their ease of use and no-compromise, high-quality audio. The R-05 model inherits this concept, packing a wide variety of great recording functions into a compact body.

Our aim is to bring high-quality recording and ease of use to the masses, no matter the skill level or budget.



*Please see product features (p. 2-3) that are shared by products in the series.

Rehearsal function automatically adjusts input to optimum levels

This feature offers a quick way to adjust input levels before recording, which simplifies the process for first-timers. Input levels can be adjusted automatically using simple button operations. This allows beginners to make high-quality recordings even if unfamiliar with recording techniques.






Pre Record function ensures that you won't miss sounds that occur suddenly

When you keep the unit in Record Standby mode, the recorder captures everything in its memory. When you press the Record button, the actual

recording begins from a point two seconds before you pressed the button. You will no longer miss important recording opportunities.



Supports simultaneous recording of WAVE and MP3

The R-05 supports simultaneous recording in WAVE (high quality) and MP3 formats (convenient for PC file exchange). There's no need for format conversion. Choose the format that best suits your needs.

Large display for better visibility

The large LCD provides an intuitive interface that's easy to use, even for beginners.

8:84:32 1

Supports over 16 hours of continuous recording on battery power

Enjoy over 16 hours of continuous recording* on batteries (two size AA batteries). The R-05 supports large-volume SDHC memory cards, which provide ample space for lengthy recordings. "Two-way power with support for AC Adaptor (sold separately)

Convenience and ease of use — the foundation of our recorders

•For hands-off recording at the perfect position, mount your R-series recorder on a standard camera tripod

- •Convert saved WAVE files (WAV) into MP3 directly onboard the unit.
- •The Auto Record Start function starts recording when a user-specified input level is reached.





Options only for R-05





Silicone Rubber Cas

R-05 picture with OP-B05C

protecting the recorder from scratches, shock, and vibration, and a windscreen for reducing noise during outdoor recordings. You can operate the recorder with both of these items attached.



AC Adapt

Binaural Microphones/Earphones

CS-10EM



In contrast to typical stereo localization, binaural record capable of reproducing real images 360° around your he above, below, front, and rea providing an accurate sense

These high-quality earphones are very comfortable to wear, a been outfitted with high-performance condenser stereo mics t deliver a flat frequency response. Wear them while you record capture sounds at the exact location you hear them. This crea amazingly realistic feel. You can also monitor your recording the the earphones while you record. The plug-in power design, while you record. power is supplied from the recorder, makes binaural recording All you have to do is connect the earphones to the unit.

•Weight: 4.5 g (without cord) •Cord: 1.5 m •Plug: Stereo mini (gold-plated) x 2 •Accessories: Carrying Pouch, Ear pieces (S, M, L)



4





Top



- 7. AC ADAPTOR jack
- 8. POWER/HOLD switch
- 9. LINE IN jack
- 10. MIC INPUT jack
- 11. SD card slot
- 12. Hook for strap

R-05 package contents

The silicone rubber case fits snualy over the unit. protecting it from scratches, dust, and dirt. It also helps reduce noise from handling or vibration that may be transmitted from the surface with OP-R05S. it's placed on



R-05, Windscreen, SD memory card, USB cable Batteries (AA x 2) Owner's manual Easy Start Guide

cording	
corung	Quality Attal. "Discourse 1 Descending of Descenting 1"
	Special Article "Binaural Recording Described"
ing is audio pad — r — e of depth.	Binaural recording is also referred to as the "both-ear effect." Recordings made using this technique, when listened to on headphones, give listeners a realistic feel of actually being in the space where the recording was made. 3D video has become all the rage in recent years, and you could call binaural sound "3D audio." Typical binaural recordings use a dummy head, simulating the human head. Small mics are placed in this dummy head near the area where human eardrums would be. The secret to reproducing 3D audio has to do with the shape of the human head and ear features. Sounds reaching our eardrums have a unique signature that is created as it reflects and refracts against body parts, including features on our ear lobes. In technical terms, this is called the head-related transfer function (HRTF). The human brain
and have	takes this sound, which has been altered through various reflections and refractions, and analyzes a variety of factors, including the differences in the
hat	volume of sound reaching the left and right ears, as well as the difference
l, and	in arrival time, to recognize the location of the sound and the space where
ites an hrough here	the sound is being made. Therefore, by recording sounds that possess the unique signature created by the physical features near our ears, and listening to them via headphones, the listener is able to hear a realistic audio image
js a snap.	as if he or she were actually in the space where the recording was made. The
	CS-10EM lets you easily make binaural recordings by wearing the stereo mic
\frown	like standard earphones. Experience 3D sound with a true realistic feel.
\bigcirc	Shobi University, Faculty of Informatica for Arts, Department of music Expression
	Professor Shun-ichi Furuyama



Mic location and angles have been designed to deliver a rich sense of stereo width

The frame portion that supports the R-09HR's mic unit is made of a metal chassis that's isolated from the circuit board. The position and


angles have been thoroughly optimized to deliver a natural sense of stereo. Packed with a variety of proprietary technologies, including an ICA omnidirectional mic system and floating construction, this recorder delivers high-quality recordings that are clear, detailed, and expansive.




Actual size

high rigidity and precise placement

Frequency Response





WAVE/MP3 RECORDER R-09HR



Every detail of this recorder has been designed to enhance the comfort of making high-quality recordings. A rubber-feel body that reduces handling noise, a convenient wireless remote controller, and a preview monitor that lets you hear your recordings on the spot are just some of the details that have gone into R-09HR. The R-09HR is recognized around the world as the de facto standard of portable recorders. 24bit/ Limiter Organic LED File Edit



*Please see product features (p. 2-3) that are shared by products in the series.

Organic LED display makes it easy to view recording levels

The R-09HR is equipped with a large organic EL display that displays a wide range of easy-to-view information, including level meters. With its

high contrast and a wide field of vision. the display provides excellent viewability indoor and out. The display is also fast and responsive, ensuring that level adjustments are always accurate.



Organic LED display

Includes a wireless remote controller

The remote lets you control functions such as Record Start/Stop and Input Level adjustments wirelessly. An LED indicator illuminates when the R-09HR is recording, and flashes when it receives excessive input. Enjoy accurate control from a distance, and prevent handling noise that typically comes from operating the unit directly by hand.



Convenient tuner and metronome functions built in

An onboard tuner and metronome are built into the R-09HR, which let you play and record with an accurate pitch and tempo reference.

KEYA AUTO AAO	Graphic Tuner	Metronome
		J 120 ●000
		Beat 4 🖳

Pro specifications and ease of use

•The R-09HR is equipped with a preview monitor for checking recordings on the spot. •The custom cover (included) has a threaded hole for attaching the recorder to a standard camera tripod (sold separately). •The R-09HR can be powered from batteries or AC (AC adaptor included)

Bundled audio-editing program adds power and versatility

The R-09HR comes with Cakewalk pyro Audio Creator LE, a multi-function audio-editing program. You can use pyro to divide, edit, process, and add effects to audio files imported from the R-09HR. It also lets you convert to a variety of audio-file formats. Pyro also has a CD-production function for burning and archiving your music to disc.



Options only for R-09HR



Common options available for the R-05 and R-09HR







to attach the R-05/R-09HR to a generic

This custom pouch is cushion-lined to

pocket for storing the included remote

(R-09HR) or spare batteries.

absorb impact. Comes with a convenient

mic stand

OP-RP1


This microphone stand adaptor allows you

Stereo microphone with support for plug-in power - ideal for external use with the R-05/R-09HR



your R-05 or R-09HR recordings. Sealed headphone design provides a secure feel with minimal fatigue when worn for extended periods.

Monitor Headphon **RH-300**





COLUMN COLUMN pyro AUDIO CREATOR LE for Windows

•Audio engine derived from Cakewalk's flagship SONAR recording/editing program •Normalization function for raising the volume of an audio file to the optimum level •Tools for noise reduction and sound-quality correction are included Supports a wide range of audio formats and file conversions For more info visit www.cakewalk.com/OEM/AudioCreator LE.asp





- 2. MIC INPUT jack
- 3. LINE IN jack
- 4. Preview Monitor
- 5. HOLD switch
- 6. LIMITER/AGC switch
- 7. PLUG-IN POWER switch
- 8. LOW CUT switch
- 9. MIC GAIN switch

- 10. (+) and (-) VOLUME buttons
- 11. POWER switch
- 12. AC ADAPTOR jack
- 13. Optical receiving port for the remote control
- 14. Remote indicator
- 15. HEADPHONE jack
- 16. USB connector
- 17. SD/SDHC memory card slot

R-09HR package contents



B-09HB Dedicated Cover AC adaptor (PSB6U) Remote control, Lithium Battery for Remote control, USB cable (mini-B cable), SD memory card, CD-ROM Cakewalk "pyro Audio Creator LE", Owner's manual





B-05/B-09HB to be mounted on the ST-100MB

Microphone stand gives you ample latitude in your settings. Special carrying pouch included



Microphone Stan

ST-100MB



Open-air design offers a natural and clear sound, as well as a comfortable fit. You can hear sounds around you while wearing these headphones



Custom carrying case for the R-05/ R-09HR, with space for AC Adaptor, cables and spare batteries

In-Ear Headphone RH-iE3



These in-ear headphones were specifically designed for playing back audio from the R-05 or R-09HR.

B-05/B-09HB Comparison Chart

	R-05	R-09HR			
Recorder					
Tracks	2 (Stereo)				
Signal Processing	AD/DA conversion: 24 bits, 44.1/48/88.2/96 kHz				
Wireless remote controller	_	0			
Preview monitor speakers	_	0			
Limiter	0	0			
AGC(Auto Gain Control)	0	0			
WAV+MP3 simultaneous rec.	0	-			
Rehearsal function	0	_			
Effects *Playback only. Excludes playb	ack in 88.2 kHz or 96 kHz.				
Reverb	4 types (Hall1, Hall2, Room, Plate) *Reverb and Speed Change can't be used at the same time.	4 types (Hall1, Hall2, Room, Plate)			
Speed Change	50 to 150 % of playback speed *Reverb and Speed Change can't be used at the same time.	50 to 150 % of playback speed			
Other					
Tuner	_	Tuner / Graphic Tuner			
Metronome	_	0			
File Edit	0	0			
Display	128 x 64 dot graphic LCD	128 x 64 dot OLED (Organic Light-Emitting Diode) display			
Power Supply	AC Adaptor, Alkaline dry battery LR6 (AA) type x 2, or Nickel-metal hydride battery (HR15/51) x 2	AC Adaptor, Alkaline dry battery LR6 (AA) type x 2, or Nickel-metal hydride battery (HR15/51) x 2			
Dimensions	59.6 (W) x 103.0 (D) x 25.0 (H) mm 2-3/8 (W) x 4-1/16 (D) x 1 (H) inches	62.0 (W) x 112.9 (D) x 270 (H) mm 2-1/2 (W) x 4-1/2 (D) x 1-1/16 (H) inches			
Weight	140 g/5 oz (including batteries)	174 g/7 oz (including batteries and memory card)			
Dedicated cover	Optional	Included			
Audio Editing Software	— Cakewalk pyro Audio Creator LE				

R-05/R-09HR System Requirements: USB Interface			
Windows		Macintosh	
OS	Microsoft® Windows® 7/Windows Vista®/XP Home/XP Professional	OS	Mac OS X 10.2 or later
Computer	Windows compatible PC equipped with a USB2.0 or 1.1 port	Computer	Apple® Macintosh® series with on-board USB port

System Requirements: Cakewalk pyro Audio Creator LE (bundled with R-09HR)

OS	Microsoft® Windows® 7/Windows Vista®/XP Home/XP Professional SP2 or later
Processor	Intel [®] Pentium [®] 4 1.3 GHz, or AMD Athlon™ XP 1500+ or higher
RAM	256 MB
Hard Disk Space	50 MB for core program
Video Resolution	1024 × 768, 16-bit
Audio Interface	Windows-compatible
Optical Drive	CD-ROM required for installation / CD-R or CD-RW capability required for CD audio disc burning

*Cakewalk pyro Audio Creator LE does not support Windows Me/98/95/NT/2000/XP Media Center Edition or XP Professional x64

*This product does not support Macintosh computers running Microsoft Windows. *This product has been tested on representative computers that meet the system requirements, but

we cannot guarantee that it will operate on any computer that meets these requirements. *This product includes a 30 day trial version of the MP3 Encoder.

For more info visit

www.roland.com/products/en/R-05/ (R-05)

www.roland.com/products/en/R-09HR/ (R-09HR)

R-05/R-09HR recordable time (approximate)

R-05/R-09HR recordable time (approximate) Units: minute							
	Rec Mode	SD/SDHC card capacity					
	Rec Mode	512 MB	2 GB	4 GB	8 GB	16 GB	32 GB
	WAV (24 bit/96 kHz)	13	55	110	220	450	900
	WAV (24 bit/88.2 kHz)	15	60	120	240	490	980
	WAV (24 bit/48 kHz)	27	110	220	440	900	1800
WAV	WAV (24 bit/44.1 kHz)	29	120	240	480	980	1950
WAV	WAV (16 bit/96 kHz)	20	80	160	320	670	1350
	WAV (16 bit/88.2 kHz)	22	88	176	352	735	1470
	WAV (16 bit/48 kHz)	40	166	332	664	1350	2700
	WAV (16 bit/44.1 kHz)	44	180	360	720	1470	2950
LID0	MP3 (320 kbps/44.1 kHz)	196	797	1540	3080	6450	12950
MP3	MP3 (128 kbps/44.1 kHz)	490	1993	3990	7980	16180	32350
WAV+MP3 (R-05 only)	WAV (16 bit/48 kHz) MP3 (128 kbps/48 kHz)	40	152	305	610	1240	2490
	WAV (16 bit/44.1 kHz) MP3 (128 kbps/44.1 kHz)	43	165	330	660	1345	2690

*Each recording time is approximate. The times may change depending on the card specifications.

*In case that there are plural files, the sum of recording time would be shorter than above.

•In the interest of product improvement, the specifications and/or appearance of this unit are subject to change without prior notice. •Microsoft and Windows are registered trademarks of Microsoft Corporation. •Windows® is known officially as:"Microsoft® Windows® operating system" •Apple and Machintosh are registered trademarks of Apple Inc. •The SD logo and SDHC logo are trademarks of SD-3C, LLC. •MPEG Layer-3 audio compression In the bill of the second seco



Printed in Japan May 2010 RAM-4595 GR-UPR-SS ACGC1

