

Wall/on-wall-ceiling-loudspeaker **RG-180F/EN5424** in full-metal-design

RG

180F

**EN
5424**



**W
A
L
L**

—

**C
E
I
L
I
N
G**

**L
O
U
D
S
P
E
A
K
E
R**

- FIRE-RESISTANT & **BALL-ATTACK-PROTECTED**
- **BALL-PROOF-DEVICE** ACCORDING TO **DIN-18032-III** OPTIONAL
- THEFT-PROTECTED MOUNTING-BRACKET & SCREWS
- **50-HZ-STABLE** TRANSFORMER
- **TOUCH-PROTECTED** 100-V-QUICK-CONNECTING-CLAMP
- **CUSTOM-COLOUR** AVAILABLE
- **WET-ROOM/DAMP-ROOM**-VERSIONS OBTAINABLE
- OPTIONAL **CERAMIC-CLAMP** & **THERMO-FUSE** AVAILABLE

- **RG-180F/EN-5424-CERTIFICATED VERSION:**
ORDER-NUMBER:

RG-180F/EN-5424
CPD-NR: 1293-CPD-0231

TECHNICAL DATA:

RG-180F/EN5424

Loudspeaker:	10/15W broadband with HF-cone
Power-Consumption:	100V-6-3-1.5W
Frequency-Range:	100-16 000 Hz
EN-Sensitivity 1W/4M:	81,0 dB
SPL max 6W/4M:	89,5 dB
SPL 1W/1M max. EASE/Ulysses:	103 dB (1,5 & 3,5 kHz)
SPL 6W/1M max. EASE/Ulysses:	109 dB (1,5 & 3,5 kHz)
Radiation H (0,5/1/2/4kHz):	115°/115°/94°/33°
Radiation V (0,5/1/2/4kHz):	115°/115°/94°/33°
Dimensions:	180 mm x 70 mm
Weight:	1 Kg
Colour:	RAL 9010

