



HD & SD HD & SD Mobile Video Recorders Studios HD & SD Monitors

\*\*\*\*\*

Converters

Chromakey

HD & SD Accessories SDI CG



Datavideo SE-900 is a modular 8-channel SD switcher with a feature set that may be expanded with additional input cards and accessories. The two piece unit consists of a 19-inch rack mountable main frame, that holds up to 8 input cards, and a control panel. The modular switcher accepts a mix of 8 SD input of your choice including DV, SDI, DVI, YUV and Composite Video. Standard outputs

include DV, YUV, S-Video (Y/C) and Composite Video.

SE-900 features a built in frame synchroniser and TBC for each channel for flicker free switching between all 8 inputs - in any format. Optional genlock input card is available for genlock to existing house reference. The preview output includes both next source and next effect, enabling the producer to preview

any effects in confidence before "going live" SE-900 features a down stream keyer for easy integration with a character generator system, such as Datavideo's CG-100 or CG-350. To accommodate for any delay in DV or SDI equipment SE-900 includes an audio delay function as well as a DV/SDI audio embedder.

# **■** FEATURES

- Up to 8 inputs available for any format including SDI, DV, DVI, VGA, YUV, Composite Video
- Outputs include SDI, DV, YUV, S-Video (Y/C) & Composite Video
- Multi image preview panel allows the producer to monitor all live sources (up to 8 input) as well as Program & Next source
- Easy adjustable audio delay for perfect video/audio sync with DV & SDI sources
- SDI Audio embedder Audio input & output includes RCA (phono) and balanced audio via XLR

- Optional dual chromakeyer, where each keyer can accept two foreground inputs and two background inputs.
- Picture in Picture
- Tally output
- GPI & RS-232 control interface for integration with existing equipment
- SDI Graphics overlay interface for optimal quality of character generator software such as Datavideo CG-100
- No genlock is required for flicker free switching thanks to the built in frame synchronisers and TBCs

## **CONTROL PANEL VIEW**



# BASE UNIT REAR VIEW



# **FEATURES**



Six pre-set speed keys, enabling the producer to set AUTO Take, Key or other pre-event.



Quick key for selection of Fade to



Joystick for RGB control or PiP position



Effect selector including PiP, Mosaic, Paint, Chromakey, Logo insert and much more



The bright LCD Screen ensures easy and confident navigation of multi functions for the producer in a live situation



Ten quick selection keys for pre-set events & effects. Makes it easy to pre-program frequently used special



Four channel virtual studios selection.




Easy installation of optional cards including SDI, DVI, Down Stream Keyer, Genlock in and more



Both Phone RCA and Balanced XI R audio connection, with advanced audio program multi image preview delay function, assuring perfect audio and video synchronization.



Each live channel, plus preview and





Optional down stream keyer (DSK) board offers both Internal and External keying options.

Perfect for integration with character generator software such as Datavideo CG-100 and CG-350



Advanced Tally feature allow easy connection to external tally systems such as Datavideo ITC-100 or TB-5





# Chromakey Studio Setup

**DV** Input

SDI Output

Board

**DVI Multi** 

Viewer Board

Board

DVI-D &

Board

**VGA Input** 


Four Channel

Chromakey

Board

Genlock

Board



# SPECIFICATIONS

#### ■ Video Input

Up to eight input in any format, choose between SDI, DV, Analogue Y:U:V, Composite Video & Y/C ( S-Video) DVI-D or VGA

### ■ Audio Input

Both Balanced XLR and RCA with audio delay for perfect sync with DV or SDI video Sources.

### ■ Audio Delay

Adjustable for accurate synchronisation between -17 to 0 frame

### ■ Video Output

Simultaneous SDI, DV, Component Y:U:V, S-video(Y/C) and Composite Video output. Additional output options include; SDI with embedded audio

### ■ Audio Ouput

RCA (Phono) and Balanced XLR ±12Vp-p

## ■ Preview Output

Each input includes a Composite output, as well as a unique multi-image preview

## ■ CG Overlay

SDI Graphics overlay interface using

Datavideo CG-100 or CG-350 utilising Blackmagic

Design™ DeckLink Card™

#### ■ Plus internal DSK

### ■Remote Control

RS-422 & RS-232 & GPI

### ■ Tally interface

D-SUB 15-PIN Group A 1-4 input, group B 5-8

#### ■ Video Correction

Video correction for each channel include; brightness, contrast, saturation and white balance.

### ■ 6 selectable transition speeds

- FTB key Fading to black, Short Cut Key
- 10-Pre-event preset keys
- 15 transition effects

# ■ Digital Effects:

PiP, Border Line, Art Paint, Mosaic and Black/White, Chromakey

### ■ Power

DC12V 10A

#### ■ Dimensions

Main Unit 430 wide x 350 high x 17.6 deep (mm)

Control Panel 430 wide x 310 high x 95 deep (mm)

### ■ Weight

Main Unit 11.4KG
Control Panel 2.6KG

# SE-900 ACCESSORIES (OPTIONAL)



TLM-700

7" TFT LCD Monitor



8-channel intercom talk back system



3 meters HD/SD YUV Cable



2 x 7" TFT LCD Monitor



DV Repeaters for long DV cable run or Distribution of DV signal



6-Pin to 4-Pin DV adapter



TLM-404



4 x 4" TFT LCD Monitor

Tally box and Tally light for camera tally



50 meter tally light extension cable between ITC-100 &



Digital Video Recorder



YUV to SDI Converter



50m/ 100m all in one cable




Digital Video Recorder



software, utilising Blackmagic
Design™ DeckLink Card™



10/20 meter DV Cable. Cable run can be extended to over 160 meter by combining 2066 with several VP-314



Network Video Server

NVS-10





Datavideo Distributor / Reseller:

# DATAVIDEO WORLDWIDE OFFICES

Datavideo Technologies Co. Ltd 10F. No. 176, Jian 1st Rd., Chung Ho City Taipei Hsien 235, Taiwan, R.O.C.

R.O.C. Tel: +886-2-8227-2888 Fax: +886-2-8227-2777 E-mail:service@datavideo.com.tw

Datavideo Technologies China Co 2 F-D, No. 2, Lane 777 West Guangzhong Rd. Zhabei District Shang-hai, China Tel: +86 21-5603 6599 Fax: +86 21-5603 6770 E-mail:service@datavideo.cn Datavideo Corporation
7048 Elmer Avenue.
Whittier, CA 90602,
U.S.A.
Tel:+1-562-696 2324
Fax:+1-562-698 6930
E-mail:contactus@datavideo.us

Datavideo Hong Kong Ltd G/F,,26 Cross Lane Wanchai, Hong Kong Tel: +852-2833-1981 Fax: +852-2833-9916 E-mail:info@datavideo.com.hk Datavideo Technologies Europe BV Floridadreef 106 3565 AM Utrecht, The Netherlands Tel:+31-30-261 96 56 Fax:+31-30-261 96 57 E-mail:info@datavideo.nl

Datavideo Technologies (S) PTE Ltd No. 22 Lorong 21A Geylang, #09-02 Prosper Industrial Bldg, Singapore 388431 Tel:+65-6749 8866 Fax:+65-6749 3266 E-mail:sales@datavideo.sg Datavideo UK Limited Unit 2 Waterside Business Park Hadfield, Glossop, Derbyshire SK13 1BE, UK Tel: 444-1457 851000 Fax: 444-1457 850964 E-mail:sales@datavideo.co.uk