

EN-H10-G

EN54-24 certified compression driver horn 10W



The unit can be used as low impedance speaker by setting

the power selector switch to the 20 ohms position. In the

100 volt position 1.25, 2.5, 5 & 10 watts can be selected.

The Apart EN-H10-G is a powerful horn speaker made of UV and impact resistant ABS (RAL 7035 equivalent), (UL94V0), equipped with a compression driver and a multi tap 100 volt transformer, all certified according EN 54-24. The IP66 rating for this horn speaker makes it the ideal choice for in- and outdoor industrial applications.

The unit is equipped with a ceramic speaker line connector block, junction box, thermal fuse and stainless installation bracket.

TECHNICAL SPECIFICATIONS

outside diam. in mm	142	depth in mm	210
loudspeaker system	compression driver	mounting system	2 screws
colour	grey	100V transformer power taps in watts	10 - 5 - 2,5 - 1,25
impedance in ohms	20		10
SPL 1W/1m in dB	98	low impedance power in watts	10
	270 424	max SPL 1m in dB	108
frequency response in Hz	370 - 13K	main construction material	ABS plastic
grille main material	ABS plastic	main construction material	Abs plastic
	Vaa	IP rating	66
applicable low impedance	Yes	applicable in 100V	Yes
certificate ref	1438/CPR/0355		105



MORE PICTURES

