Infinitely Expandable Multi-Plasma




THE **BREAKTHROUGH** OF ULTRA-LARGE COMMERCIAL DISPLAY



## OZIONPDP

4F., ILSHIN BLDG., 15-15, YEOUIDO-DONG, YEONGDUNGPO-GU SEOUL, REPUBLIC OF KOREA TEL: 82-2-6678-8505 FAX: 82-2-6678-8599 sales@oriondisplay.net www.oriondisplay.net





### **Ultimate Plasma Evolution**

ORION PDP's new MPDP improves continuity of image as the Seam size is below 4mm. By removing sidecovers, viewers can see bigger images without distortion on the screens.














**Conventional Multi-PDP** 



**Seamless Technology** 





New MPDP


Rear Projection

Using plasma technology, MPDP saves room and minimizes weight considerably compared to other large displays such as rear projection systems.

As total thickness is just 25cm including stand or wall-mount brackets, MPDP is the right choice for large display in a confined space.


### **Product line-up**

Shops, banks, cinemas, control rooms, exhibitions & events, etc.. Name your need, we have the perfect digital solution prepared. Various types of MPDP to fit your specific needs.




# **INDOOR VENUE**

CONFERENCE ROOM / WORSHIP HALL / BANK



▶ Insertion of black stripes greatly enhances the black level and also the contrast ratio.



## **MIS-4220**

### **KEEP YOUR LIGHTS ON**

The appliance of the black stripes on the panel greatly enhances the black level, combined with the high brightness results in a high contrast ratio allowing the MPDP's to display clearly in bright environments.

Indoor applications such as conference room, church, mosque, broadcasting studio, bank, movie theatre where large displays need to be deployed, the seamless MPDP will be the perfect solution without dimming or turning off your lights.



WORSHIP HALL **Korea** 5 × 5



NEWS STUDIO Romania 4×3



BANK Hong Kong 10×3



MOVIE THEATRE Turkey

## **RETAIL SIGNAGE**

SHOPPING MALL / DEPARTMENT STORE / RESTAURANT



▶ Equipped with Anti-Glare Anti-Reflection filter film for a sharp and a clear display.





## **MIS-4220**

### **GO AHEAD, GO DIGITAL!**

Fed up with the same old boring still signage?
Bring a change into your stores and malls with a lively digital solution using our MPDP. The freeness in configuration gives you a variety of

designs to fit into your requirements.

Lighting and daylight was a problem for retail signage applications due to glare and reflection. Coated with an AGAR(Anti-Glare & Anti-Reflection) filter film, the new MPDP reduces the glares and reflections allowing the display to be shown clearly even in semi-outdoor applications.



SHOPPING MALL Saudi Arabia  $3 \times 3$ 



DEPARTMENT STORE United Kingdom  $2 \times 2$  Portrait




DUTY FREE SHOP Singapore  $6 \times 3$ 




SHOPPING MALL Australia  $2 \times 1$ 

# **COMMAND & CONTROL**

SURVEILLANCE / UTILITY CONTROL / SIMULATION ROOM



▶ Burn In Compensation(BIC) technology applied for the MIS-4230/4230R



## MIS-4230/4230R

### **BURN-IN-COMPENSATION(BIC)**

Previously, plasma displays had difficulties to enter control room applications where most of the displaying contents were either static or repetitive causing severe burn-in problems. However, the MIS-4230/4230R armed with BIC technology will give a compensation of over 80% with a couple of adjustments in the first year of running.

The MIS-4230/4230R adopts the BIC technology to allow MPDP to be a solution for control rooms. Compared to the high initial and maintenance cost of previous solutions, the BIC applied MPDP(MIS-4230/4230R) provides quality and space efficiency with a budget much smaller.



COAL MINING CENTER China  $4 \times 4$ 



DISASTER CONTROL CENTER
Turkey
5 × 4



UTILITY CONTROL ROOM
Mexico
8 × 4



SIMULATION ROOM Norway 3×2 on 5×2


## **RENTAL & STAGING**

BROADCASTING / MOTOR SHOW / CONFERENCE / FASHION SHOW




### Fortified edges suitable for rental applications

MIS-4220 / MIS-4230



MIS-4220R / MIS-4230R with Side Cover



## MIS-4220R/4230R

### **DURABILITY VS. PERFORMANCE**

In rental applications where you set up and pull down the installation regularly, the durability will be preferred than a minor loss in performance.

The 'R' type models are specifically designed to fit the needs of temporary installation by adding metal side covers for extra protection of the panel. Just a little increase in the seam size by 2mm allow you to handle the sets with much ease.

The 4230R model also has the additional function of Burn-In-Compensation for long-term rentals using static or repetitive images and contents.



TELEVISION SHOW Korea  $(1 \times 3 \text{ Portrait}) \times 6$ 



 $\begin{array}{c} \text{MOTOR SHOW} \\ \textbf{Indonesia} \\ 20 \times 2 \end{array}$ 



 $\begin{aligned} & \text{CONFERENCE EVENT} \\ & \textbf{Argentina} \\ & 4 \, \times \, 4 \end{aligned}$ 




FASHION SHOW United Kingdom 4×4

## **SPECIFICATION**


Model Name	MIS-4220	MIS-4220R	MIS-4230	MIS-4230R	
Power supply		100 ~ 240V AC. 50/60Hz			
Power consumption					
Average (Typical)	300W				
Max	360W				
Plasma display panel		42 inch, 16:9 Aspect Ratio			
Contrast ratio		10,000 :1 (Dark Room)			
Brightness	1,000 cd/m² (W/O Film)		1,000 cd/m² (Without film & BIC)		
Burn-in effect			Burn-In Com	pensation (BIC)	
Front filter		AGAR (Anti Glare Anti Reflection)			
Number of pixels		853(H) X 480(V)			
Seam gap (In case of multi formation)	≤ 4mm	≤ 6mm	≤ 4mm	≤ 6mm	
Environmental condition					
Temperature		0°C~ 35°C			
Humidity	20% ~ 70%				
Signal					
Video signal		NTSC, PAL, SECAM			
PC signal		SVGA, WVGA, XGA, SXGA, WXGA, UXGA			
Frequency		Horizontal Frequency 15.5 ~75kHz Vertical Frequency 50/60Hz			
Connectors	In	Input		Output	
Video	CVBS : BNC 1pin	CVBS : BNC 1pin			
	S-Video : DIN 4pin	S-Video : DIN 4pin			
Component	Y, Pb, Pr : BNC 3pin	Y, Pb, Pr : BNC 3pin Same as left side PC RGB : D-Sub 15pin		s left side	
PC	PC RGB : D-Sub 15pin				
DVI	TMDS : DVI-D 24pin		1		
Serial	RS-232C D-Sub 9pin(fer	RS-232C D-Sub 9pin(female) RS-232C D-Sub 9pin (male)		Sub 9pin (male)	
Weight		26kg (±1kg)			

### EXTERNAL DIMENSION

#### + MIS-4220 / MIS-4230




#### + MIS-4220R / MIS-4230R



## **CONNECTION**

### CONNECTING MPDP

· Each screen is connected through Daisy Chain(Link)



### MSCS (Multi Screen Control System)

- ${\boldsymbol{\cdot}}$  User friendly control program supplied with the monitor
- Controllable upto 15\*15



Main Image of MSCS (Multi Screen Control system)

PRODUCT LINE-UP

## **FEATURE**

### INPUT /OUTPUT TERMINAL



#### 1. RS-232C

Multi-PDP Control, Firmware Upgrade, 9pin D-sub

#### 2. Video

Composite Signal NTSC, PAL, SECAM

### 3. S-Video

S-Video Signal NTSC, PAL, SECAM, 4pin Mini Din

4. Component

DVD Signal

DTV - YPbPr Signal

#### 5. PC

Computer RGB Analog Signal, D-sub 15pin

### 6. DVI-D

TMDS Signal

### 7. ID Switch

Set ID Switch

#### 8. AC Input

AC 100V ~240V, 50/60Hz

### FEATURE

- · Advanced digital circuit design
- · Adopted exclusive digital processor
- · User friendly remote control as well as RS-232C control
- · Auto detection of NTSC, PAL, SECAM
- · Image quality enhancement
- 3D comb filter(Y/C separation)
- · Motion adaptive de-interlacing
- · Global Offset/Film mode support/Inter field noise reduction

#### RS-232C CONTROL

- Power ON/OFF
- Input Select
- PC, DVI, DTV, DVD, S-video, Video
- Picture Adjustment
- Contrast, Brightness, Sharpness, Color, Tint
- Auto Tracking

- · White Balance
- Design Select
- Last Design/New Design
- ON/OFF Timer
- Slideshow
- · Video-wall Configuration
- X\*Y Matrix

### **VARIOUS MULTI DESIGNS**














## **ACCESSORIES**

### UNIVERSAL FRAME UNIT

- · Combine 'Main Frame' and 'Wall Bracket' for a wall hanging configuration.
- · Combine 'Main Frame' and 'Stand Foot' for a floor standing configuration.




### CONTROL ACCESSORIES





- Remote Control RS-232 Booster
- BIC Controller(For MIS4230/ MIS4230R)



RS-232C Distributor

