



LBB 1949/00 Gooseneck Condenser Microphone



- ▶ **Unidirectional condenser microphone**
- ▶ **Flexible stem**
- ▶ **Phantom powered by amplifier**
- ▶ **On/off sliding switch with priority contact**
- ▶ **Supplied with fixed 2 m (78 in) cable and lockable DIN connector**
- ▶ **Separate DIN to XLR adapter**

The gooseneck microphone is a stylish high quality unidirectional condenser microphone, mainly intended for public address applications.

Functions

The flexible stem base has a screw fitting, and the microphone comes with a multi-thread adaptor (3/8", 1/2", and 5/8") for mounting onto floor-stands, lecterns, panels or desktops. The microphone runs off the phantom power supply from the amplifier to which it is connected.

The on-off sliding switch, not only switches on the microphone, but also provides priority contacts for remote control switching purposes. If the priority contacts are not required, the microphone can be connected to amplifiers with 3-pin XLR-inputs, using the DIN to XLR adapter.

Certifications and Approvals

Region	Certification
Europe	CE Declaration of Conformity
Immunity	acc. to EN 55103-2
Emission	acc. to EN 55103-1

Parts Included

Quantity	Component
1	LBB 1949/00 Gooseneck Condenser Microphone
1	DIN to XLR adapter

Technical Specifications

Electrical*

Phantom power supply

Voltage range	12 to 48 V
Current consumption	<8 mA

Performance*

Sensitivity	0.7 mV @ 85 dB SPL (2 mV/Pa)
Maximum input sound level	110 dB SPL
Distortion	<0.6% (maximum input)
Equivalent input noise level	28 dBA SPL (S/N 66 dBA ref. 1 Pa)
Frequency response	100 Hz to 16 kHz
Output Impedance	< 200 ohm

* Technical performance data acc. to IEC 60268-4

Mechanical

Dimensions (D x L) 30 x 500 mm (19.69 x 1.18 in)

Weight Approx. 300 g (10.5 oz)

Color Dark gray

Cable length 2 m (78 in)

Connector 5-pin DIN 180° (lockable)

Environmental

Operating temperature -10 °C to +55 °C (+14 °F to +131 °F)

Storage temperature -40 °C to +70 °C (-40 °F to +158 °F)

Relative humidity <95%

Ordering Information

LBB 1949/00 Gooseneck Condenser Microphone **LBB1949/00**

unidirectional condenser microphone with flexible stem

Accessories

LBC 1208/40 Microphone Cable **LBC1208/40**
3-pin XLR; 10 m (32.8 ft)

Americas:
Bosch Communications Systems
12000 Portland Avenue South
Burnsville, Minnesota 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2600
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by