


**Net Price List PROFESSIONAL USER**

ALL PRICES AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Pro-Sound &amp; Lighting Solutions

www.pro-technica.com

**Price List 09 / 2014**

Effective September 21-sth, 2014

Subject to change without prior notice.









All former price lists expire with the publishing of this version.






















All prices are suggested net retail prices; ex works.

There are applicable our General Terms of Business, only.



















# EUR

Articles marked \* will be discontinued soon!

















E C P B R	Model	Description	EUR	
			Netto (ex. VAT)	+ 20% DDS (incl. VAT)
<b>Headphones</b>				
	<b>DJ-810</b>	Professional DJ headphones; stylish foldable design and unique appearance, the whole design is in accord with somatology Impedance: 64 Ohm; Sensitivity: 107±3dB; Frequency Response: 5Hz-30kHz; Max. Power: 3500mW; Cable Length: 1.5 m spring cable (about 4m fully extended); Plug: 3.5mm+ 6.3mm stereo	19,00	<b>23,00</b> EUR
<b>Wireless mic</b>				
	<b>NEW</b> <b>WMS-10/WMS-10HT</b>	VHF wireless handheld microphone for Karaoke bar, Piano bar. Appropriate for use from audience. Receiver spec: Channel frequency: 170-260 MHz Sensitivity: -95 dBm RF Image rejection:-75 dB Audio dynamic range: 95 dB (T.H.D.<1%) Freq. stability: +/- 0.002% S/N ratio:>70dB Dimensions: 16.9x12.3.7 cm Handheld transmitter spec: Carrier frequency: 170-260 MHz RF power output:> 13dBm Modulation degree:> 30kHz Power current: < 110 mA Freq. stability: +/- 0.002% Modulation: FM Batteries: 2 x 1.5V AA Dimensions: 23.8x5x5 cm	27,00	<b>32,00</b> EUR
	<b>WMS-15/WMS-15HT</b>	UHF Wireless handheld microphone - Single channel, Max. deviation+/- 40kHz, 2 x 1,5V AA, RF Output: 10 dBm, Diversity receiver, Receiving Sensitivity:>-105 dBm Frequency: 460-970MHz T.H.D.: <1% Power supply: DC 13-15V, 200mA (included) Handheld transmitter HT-15, Modulation: FM RF, Output Power: 10 dBm, Maximum deviation: +/- 40KHz Battery: 2x1, 5V AA . Includes: Receiver - WR-15 , Transmitter - Handheld HT-15 Microphone , Power supply, cables, batteries	42,00	<b>50,00</b> EUR
	<b>NEW</b> <b>WMS-15/WMS-15PT</b>	UHF Wireless Lavalier microphone - Single channel, Max. deviation+/- 40kHz, 2 x 1,5V AA, RF Output: 10 dBm, Diversity receiver, Receiving Sensitivity:>-105 dBm, pocket transmitter. Frequency: 460-970MHz T.H.D.: <1% Power supply: DC 13-15V, 200mA (included) Bodypack transmitter PT-15, Modulation: FM RF, Output Power: 10 dBm, Maximum deviation: +/- 40KHz Battery: 2x1, 5V AA Dimensions: 105mm x 65mm x 30mm. Includes: Receiver - WR-15 station Transmitter - Bodypack PT-15 Microphone - lavalier Power supply, cables, batteries	42,00	<b>50,00</b> EUR
	<b>WMS-35/WMS-35HT</b>	UHF Wireless handheld microphone - 16 Ch. Max. deviation+/- 68 kHz 2 x 1,5V AA, RF Output: 10 dBm, Diversity receiver, Receiving Sensitivity:>-105 dBm	83,00	<b>100,00</b> EUR
	<b>WMS-35DUAL/ WMS-35HT</b>	Dual UHF Wireless handheld microphone - 16 Ch. Max. deviation+/- 68 kHz, 2 x 1,5V AA, RF Output: 10 dBm, Diversity receiver, Receiving Sensitivity:>-105 dBm	125,00	<b>150,00</b> EUR
	<b>WMS A4</b>	46 ch. UHF Wireless system, 2 X AA 1,5V, XLR Sym. Out	133,00	<b>160,00</b> EUR
	<b>WMS C10-H</b>	Recharging unit for two WMS A4	24,00	<b>29,00</b> EUR
	<b>WMS-A5/WMS-A5HT</b>	UHF Wireless handheld microphone - 48 Ch. Max. deviation+/- 68 kHz 2 x 1,5V AA, RF Output: 10 dBm, Diversity receiver, Receiving Sensitivity:>-105 dBm	125,00	<b>150,00</b> EUR
	<b>WMS-A5/WMS-A5PT</b>	UHF Wireless lavalier microphone - 48 Ch. Max. deviation+/- 68 kHz 2 x 1,5V AA, RF Output: 10 dBm, Diversity receiver, Receiving Sensitivity:>-105 dBm	125,00	<b>150,00</b> EUR
	<b>AS-204TNC</b>	UHF Antenna splitter 1 x 4, 19" rack mountable, TNC connectors, Input to Output gain +3 dB	125,00	<b>150,00</b> EUR
	<b>AA-100TNC</b>	UHF antenna booster Gain - 15 d B, TNC 50 Ohm connectors, Power supply 9 V DC, supplied through connecting antenna cable from AS-204 TNC	42,00	<b>50,00</b> EUR
<b>NEW</b> 	<b>ME-2L</b>	Lavalier microphone. Polar pattern: unidirectional, Mic diameter 6 mm, Sensitivity: -47 dB+/-2 db, Freq. Range 20 Hz - 20 kHz, 3,5 mm screw jack connector (compatible to Sennheiser transmitters)	13,00	<b>16,00</b> EUR
	<b>ME-4L</b>	Lavalier microphone. Polar pattern: unidirectional, Mic diameter 6 mm, Sensitivity: -47 dB+/-2 db, Freq. Range 20 Hz - 20 kHz, 3,5 mm screw jack connector (compatible to Sennheiser transmitters)	20,00	<b>24,00</b> EUR
	<b>HS-102Beige</b>	Headset Back Electret Condenser. Color: Beige, Omnidirectional, Freq response: 100 Hz - 10 Khz, Sensitivity -42 dB+/- 2 dB (0 dB= 1V/Pa @ 1 KHz)	23,00	<b>28,00</b> EUR
	<b>HS-104Beige</b>	Headset Back Electret Condenser. Color: Beige, Unidirectional, Freq response: 20 Hz - 20 Khz, Sensitivity -47 dB+/- 2 dB, SNR > 58 dB, Mic diam. 6 mm	23,00	<b>28,00</b> EUR

EC PBR	Model	Description	EUR Netto (ex. VAT)	EUR + 20% DDS (incl. VAT)	
<b>Wireless In ear monitor</b>					
	<b>WIEM-200 set</b>	UHF Wireless In ear Monitor system. 48 preprogrammed frequencies available within 25 MHz RF bandwidth, Built-in limiter, Front panel monitoring headphone jack, Receiver output power 2x50 mW, Earphone impedance > 16 Ohm, Freq. Response 80 - 15 000 Hz, 2 x 1,5 V AA batteries	225,00	<b>270,00</b> EUR	
	<b>WIEM-200RCV</b>	Receiver for wireless IEM system - output power 2x50 mW, Earphone impedance > 16 Ohm, Freq. Response 80 - 15 000 Hz, 2 x 1,5 V AA batteries	157,00	<b>188,00</b> EUR	
<b>NEW</b>		<b>WIEM 150 set</b>	UHF Wireless In ear Monitor system. 16 preprogrammed frequencies available within 24 MHz RF bandwidth, audio - 40-14000 Hz, mix/stereo operation, S/N >90 dB, limiter,	168,00	<b>202,00</b> EUR
<b>NEW</b>		<b>WIEM 150 rcv</b>	receiver for WIEM 150 set - 2x AA batteries, 150 mA, 40-14 000 Hz, S/N>90 dB, sens. -107 dB, output 2x 50mW,S/N 94 dB	85,00	<b>102,00</b> EUR
	<b>WIEM 100 R</b>	Additional pocket receiver for WIEM 100 set	44,00	<b>53,00</b> EUR	
<b>Speaker enclosure</b>					
		<b>PS -8</b>	8" + 1.3" 2way speaker, Full Bandwidth 2-way Element (60Hz-21kHz), Sensitivity : 94dB (1M/1W), Max. SPL : 118dB, 200W long term power capacity, Nominal impedance : 8 ohm Very Compact, Lightweight plywood construction, 2way configuration with internal passive crossover, 75°(H) x 65°(V) Horn with variable Dispersion (rotatable), Multi-flying point (All flying accessories included), 200W@8ohm high efficiency 8-in LF transducer (3"VC) with fibre glass horn loaded 1.3-in compression driver	150,00	<b>180,00</b> EUR
		<b>PS -10 II</b>	10" + 1" two-way full range professional speaker system, Frequency response : 60-18kHz, Sensitivity : 95dB (1M/1W), Max. SPL : 121dB, 300W long term power capacity, Nominal impedance : 8 ohm Very Compact, Lightweight plywood construction, 2way configuration with internal passive crossover, 75°(H) x 55°(V) Horn with variable Dispersion (rotatable), Multi-flying point (All flying accessories included), 300W@8ohm high efficiency 10-in LF transducer (3,5"VC) and fibre glass horn loaded 1.3-in compression driver	170,00	<b>204,00</b> EUR
		<b>PS -12 II</b>	12" + 1" two-way full range professional speaker system, Frequency response : 55-18kHz, Sensitivity : 98dB (1M/1W), Max. SPL : 125dB, 350W long term power capacity, Nominal impedance : 8 ohm Very Compact, Lightweight plywood construction, 2way configuration with internal passive crossover, 75°(H) x 55°(V) Horn with variable Dispersion (rotatable), Multi-flying point (All flying accessories included), 350W@8ohm high efficiency 12-in LF transducer (3,5"VC) and fibre glass horn loaded 1.3-in compression driver	200,00	<b>240,00</b> EUR
		<b>PS -15 II</b>	15" + 1" two-way full range professional speaker system, Frequency response : 45-18kHz, Sensitivity : 99dB (1M/1W), Max. SPL : 128dB, 400W long term power capacity , Nominal impedance : 8 ohm Very Compact, Lightweight plywood construction, 2way configuration with internal passive crossover, 75°(H) x 55°(V) Horn with variable Dispersion (rotatable), Multi-flying point (All flying accessories included), 400W@8ohm high efficiency 15-in LF transducer (3,5"VC) and fibre glass horn loaded 1.3-in compression driver	250,00	<b>300,00</b> EUR
		<b>PS -18 II</b>	18"(4") High Power Compact Subwoofer - Power (RMS) 600 Watts, Power (Peak) 2400 Watts , Frequency Response 35Hz ~ 250Hz, 100mm Voice Coil, Nominal Impedance 8 ohm , Sensitivity 99dB, Max SPL 128dB, Dimensions (HxWxD) 670 x 510 x 686mm , Cabinet materials 18mm MDF, Finishing Textured black	300,00	<b>360,00</b> EUR
<b>VOLUME CONTROLS</b>					
<b>NEW</b>		<b>VC-6300</b>	Volume Control for 6 pairs of stereo speakers with total power 300W, A/B source amplifier switching, total attenuation 42 dB, Attenuation positions 12, Dimensions 425x260x63 mm	150,00	<b>180,00</b> EUR
<b>CONFERENCE SYSTEMS</b>					
	<b>MC-600</b>	Supports up to 50 mic units; expandable, AUX, MIE and telephone in; 2 LINE outs, 2 x 50 W Speaker Outputs	125,00	<b>150,00</b> EUR	
	<b>MC-601</b>	Takes priority over other microphone units, Push to talk; internal speaker; LED indicator, Desktop stand; flexible gooseneck stem	75,00	<b>90,00</b> EUR	
	<b>MC-602</b>	Delegate operated microphone unit, Push to talk; internal speaker; LED indicator, Desktop stand; flexible gooseneck stem	45,00	<b>54,00</b> EUR	
<b>MUSIC SOURCE</b>					
		<b>AP-W218K</b>	Dual playback; single record decks, Dolby B/C; MPX filter, Automatic playback / record	50,00	<b>60,00</b> EUR



















EC PBR	Model	Description	EUR Netto (ex. VAT)	EUR + 20% DDS (incl. VAT)
<b>Digital Speaker Processors</b>				
	<b>DS 24</b>	Speaker management processor : 2 Inputs /4 Outputs, *Gain and 3Bands PEQ on each input HPF, LPG snf 5 bands EQ on each output * Polarity control on each output, Up to 8ms delay * Limiter function on each output * USB port,16 user memories	130,00	<b>156,00</b> EUR
<b>Amplifiers</b>				
<b>Poweramplifier DA Series</b>				
	<b>DA 6.1 / DA 6.2</b>	AUDIOCENTER Class AB Poweramplifier <b>2 x 840W 4 Ohm</b> , 2500W Bridge 4 Ohm, <b>Damping Factor &gt; 2000!!!, Slew Rate ≥260V/us !!!</b> Phase response +/-5°, 20Hz-20kHz+0.3dB, S/N Ratio more than 104dB. ● TourClas features: ACL, IGM, AutoRamp, Ground Lift, Subsonic Filter ● Full protection: Short circuit; Overload protect, DC protect, Soft start, Thermal protect XLR Sym. Input, Data Input; 2 Variable Rear Fans, 2HE, 23 kg	350,00	<b>420,00</b> EUR
	<b>DA 9.1</b>	AUDIOCENTER Class H Poweramplifier <b>2 x 1350W 4 Ohm</b> , 4000W Bridge 4 Ohm, <b>Damping Factor &gt; 2000!!!, Slew Rate ≥260V/us !!!</b> Phase response +/-5°, 20Hz-20kHz+0.3dB, S/N Ratio more than 105dB. ● TourClas features: ACL, IGM, AutoRamp, Ground Lift, Subsonic Filter ● Full protection: Short circuit; Overload protect, DC protect, Soft start, Thermal protect XLR Sym. Input, Data Input; 2 Variable Rear Fans, 3 HE, 35 kg	580,00	<b>696,00</b> EUR
<b>Poweramplifier PRO Series</b>				
	<b>PRO 4.0</b>	AUDIOCENTER Class AB Poweramplifier <b>2 x 600W 4 Ohm</b> , 1800W Bridge 4 Ohm, <b>Damping Factor &gt; 600!!!, Slew Rate ≥25V/us !!!</b> Phase response +/-10°, 20Hz-20kHz+1dB, S/N Ratio more than 100dB. ● TourClas features: ACL, IGM, AutoRamp, Ground Lift, ● Full protection: Short circuit; Overload protect, DC protect, Soft start, Thermal protect XLR Sym. Input, 2 Two speed Fans, 2HE, 18 kg	250,00	<b>300,00</b> EUR
	<b>PRO 6.0</b>	AUDIOCENTER Class AB Poweramplifier <b>2 x 840W 4 Ohm</b> , 2400W Bridge 4 Ohm, <b>Damping Factor &gt; 600!!!, Slew Rate ≥25V/us !!!</b> Phase response +/-10°, 20Hz-20kHz+1dB, S/N Ratio more than 100dB. ● TourClas features: ACL, IGM, AutoRamp, Ground Lift, Subsonic Filter ● Full protection: Short circuit; Overload protect, DC protect, Soft start, Thermal protect XLR Sym. Input, 2 Two speed Fans, 2HE, 21 kg	299,00	<b>359,00</b> EUR
	<b>PRO 9.0</b>	AUDIOCENTER Class H Poweramplifier <b>2 x 1500W 4 Ohm</b> , 4400W Bridge 4 Ohm, <b>Damping Factor &gt; 600!!!, Slew Rate ≥25V/us !!!</b> Phase response +/-10°, 20Hz-20kHz+1dB, S/N Ratio more than 100dB. ● TourClas features: ACL, IGM, AutoRamp, Ground Lift, Subsonic Filter ● Full protection: Short circuit; Overload protect, DC protect, Soft start, Thermal protect XLR Sym. Input, 2 Two speed Fans, 3HE, 34 kg	499,00	<b>599,00</b> EUR
<b>Poweramplifier MX Series</b>				
	<b>MX 3200</b>	AUDIOCENTER Class AB 3 Ch. Poweramplifier <b>2 x 350W (Mid/High) 4 Ω + 850W (Sub) 4 Ω</b> , <b>Damping Factor &gt; 300!!!, Slew Rate ≥15V/us !!!</b> Phase response +/-30°, 20Hz-20kHz+1dB, S/N Ratio more than 100dB. ● Features: Internal X-over, ACL, IGM ● Full protection: Short circuit; Overload protect, DC protect, Soft start, Thermal protect ● Connector for professional installation - XLR + Jack combo provides flexible connection. - PHOENIX-type output connectors allow for quick and easy connection in fixed installation. - RCA connectors provide more flexibility. 2 Two speed Fans, 2HE, 25 kg	400,00	<b>480,00</b> EUR
	<b>MX 4200</b> <b>NEW</b>	AUDIOCENTER Class AB 4 Ch. Poweramplifier <b>4 x 210W 4 Ω , 2 x 420W</b> Bridge 4 Ω , <b>Damping Factor &gt; 300!!!, Slew Rate ≥15V/us !!!</b> Phase response +/-30°, 20Hz-20kHz+1dB, S/N Ratio more than 100dB. ● Features: Internal X-over, ACL, IGM ● Full protection: Short circuit; Overload protect, DC protect, Soft start, Thermal protect ● Connector for professional installation - XLR + Jack combo provides flexible connection. - PHOENIX-type output connectors allow for quick and easy connection in fixed installation. - RCA connectors provide more flexibility. 2 Two speed Fans, 2HE, 19 kg	336,00	<b>403,00</b> EUR
	<b>COS 100</b>	4 x 180 constant-voltage transformer for 70V/100V outputstage	131,00	<b>157,00</b> EUR
<b>Poweramplifier Lexon Pro Series</b>				
	<b>Lexon Pro 900LX</b> <b>NEW</b>	<b>2 x 450 W (4 Ohm) SMPS amplifier</b> Power Output: 8 Ohm: 310 W / 950W Bridge mode @ 4 Ohm: 450 W / 1200W Bridge mode / @ 2 Ohm: 600 W XL series also has a special function selection switch for add low frequency in low sound pressure. When select this function, the low frequency (110Hz~130Hz) will add 3dB gain so you can feel a mighty low frequency in low sound pressure. XL series adopt binding post and NL4 speakon in output terminal,easy to connect to speakers.	199,00	<b>239,00</b> EUR
	<b>Lexon Pro 1500LX</b> <b>NEW</b>	<b>2 x 750 W (4 Ohm) SMPS amplifier</b> Power Output: 8 Ohm: 450 W / 1500 W Bridge mode @ 4 Ohm: 750 W / 2000 W Bridge mode / @ 2 Ohm: 1000 W XL series also has a special function selection switch for add low frequency in low sound pressure. When select this function, the low frequency (110Hz~130Hz) will add 3dB gain so you can feel a mighty low frequency in low sound pressure. XL series adopt binding post and NL4 speakon in output terminal,easy to connect to speakers.	280,00	<b>336,00</b> EUR
	<b>Lexon Pro 2000LX</b> <b>NEW</b>	<b>2 x 1000 W (4 Ohm) SMPS amplifier</b> Power Output: 8 Ohm: 600 W / 2000 W Bridge mode @ 4 Ohm: 1000 W / 2600 W Bridge mode / @ 2 Ohm: 1250 W XL series also has a special function selection switch for add low frequency in low sound pressure. When select this function, the low frequency (110Hz~130Hz) will add 3dB gain so you can feel a mighty low frequency in low sound pressure. XL series adopt binding post and NL4 speakon in output terminal,easy to connect to speakers.	320,00	<b>384,00</b> EUR


Model	Description	EUR Netto (ex. VAT)	EUR + 20% DDS (incl. VAT)
<b>MEGAPHONE</b>			
 <b>NEW</b>	<b>MP-6608</b> Megaphone with USB input. Rated/Maximum Power: 25/50W, Sensitivity: 108dB/1W/1m, Voice Range 700m, Power 8xUM-1 battery, Battery life 8-10hours Dimensions $\Phi$ 230x350mm, Net Weight: 1.5kg, without battery	36,00	<b>43,00</b> EUR
<b>ACTIVE (POWERED) CEILING SPEAKER</b>			
 <b>NEW</b>	<b>PHA-103P1</b> 5" Active Ceiling Speaker, Rated/Maximum Power: 3/6W, Power 220V AC 50-60Hz, Line In: 4.7kOhm, 6V, balanced, Frequency response 60 Hz-20 kHz, THD<0.5%; S/N Ratio: >65dB, Damping Factor 200, Dimensions $\Phi$ 240x151mm, Net Weight: 1,24kg	50,00	<b>60,00</b> EUR
<b>ELA 100V SPEAKERS</b>			
	<b>AK-601</b> 6,5" Rated Power: 6W, Line Voltage: 100V 1,5W/3W/6W, SPL (6W): 93 dB, Frequency Response: 90HZ-18KHZ, $\Phi$ 215 mm, Hole For Mounting: $\Phi$ 183mm, Metal grill	9,20	<b>11,00</b> EUR
	<b>CH-715</b> 4,5" Rated Power: 6W, Line Voltage: 100V 1,5W/3W/6W, Sensitivity (1m , 1w): 90dB, Frequency Response: 150HZ-15KHZ, Mounting: $\Phi$ 150,Enclosure: Plastic, metal grille, $\Phi$ 180 mm	3,20	<b>3,80</b> EUR
	<b>L-805T</b> 8" Rated Power: 3/6W /100V, Freq. response 80 Hz - 18 kHz, Sensitivity 93dB/1W/1m, Dimensions: $\Phi$ 265x85mm, Mounting hole diameter: $\Phi$ 240mm	9,00	<b>10,80</b> EUR
	<b>L-623</b> 6" Rated Power: 3/6W /100V, Freq. response 100 Hz - 15 kHz, Sensitivity 93 $\pm$ 3dB/1W/1m, $\Phi$ 175x60mm, Hole for mounting $\Phi$ 150 mm	5,00	<b>6,00</b> EUR
	<b>L-213</b> 2,5" Rated Power: 6W /100V, Freq. response 120 Hz - 20 kHz, Sensitivity 87 $\pm$ 3dB/1W/1m, $\Phi$ 103x80mm, Hole for mounting $\Phi$ 95 mm	5,00	<b>6,00</b> EUR
	<b>L443K</b> 4" Bathroom ceiling Speker - 6W (3/6W) /100V, 91dB/1W/1m, 150Hz-18kHz, <b>waterproof</b> , $\Phi$ 140x130mm	10,00	<b>12,00</b> EUR
	<b>L-243</b> 4" Ceiling Speaker 3/6W/100V, Freq. response 100Hz-20kHz, Sensitivity 91 dB/1W/1m, ( <b>Fireproof</b> ) $\Phi$ 135x80mm, Hole for mounting $\Phi$ 105 mm	6,00	<b>7,20</b> EUR
	<b>CH-721H</b> 6,5" Co-axial Woofer and Tweeter <b>2-Way</b> , Rated Power: 3/6W, Line Voltage: 100V, Sensitivity (1m , 1w): 94 $\pm$ 3dB, Frequency Response: 80Hz-18kHz, Mounting: $\Phi$ 198mm, Enclosure: Metal, metal grille, metal fire dome	10,00	<b>12,00</b> EUR
	<b>L-511THS</b> 5" <b>2-Way</b> Ceiling Speaker - 2.5/5/10/20W/100V, Frequency response 100 Hz-20 kHz, Sensitivity 88 $\pm$ 3 dB/1W/1m, Dimension $\Phi$ 203x145 mm, Hole for mounting $\Phi$ 170 mm, with steel cover	17,00	<b>20,40</b> EUR
	<b>L-611THS</b> 6" <b>2-Way</b> Ceiling Speaker - 3.8/ 7.5/ 15/ 30W /100V, Frequency response 90 Hz-20 kHz, Sensitivity 88 $\pm$ 3 dB/1W/1m, Dimension $\Phi$ 230x150 mm, Hole for mounting $\Phi$ 200 mm, with steel cover	20,00	<b>24,00</b> EUR
	<b>L-811THS</b> 8" <b>2-Way</b> Ceiling Speaker - 5/10/20/40W /100V, Frequency response 50 Hz-20 kHz, Sensitivity 88 $\pm$ 3 dB/1W/1m, Dimension $\Phi$ 270x185mm, Hole for mounting $\Phi$ 240 mm, with steel cover	25,00	<b>30,00</b> EUR
	<b>L-528T</b> 5" Wall In-fitted, Rated Power: 1.5/3/6W /100V, Freq. response 110 Hz - 18 kHz, Sensitivity 92dB/1W/1m, Dimensions: 190x190x80mm, Mounting hole: 160x160mm	8,00	<b>9,60</b> EUR
	<b>L-518T</b> 5" <b>Woofer + 1" Tweeter</b> Wall In-fitted <b>2 Way</b> Speaker 20W (5/10/20W)/100V, 89dB/1W/1m, 90Hz - 18kHz, 190x190x80mm	29,40	<b>35,30</b> EUR
	<b>L-622</b> <b>2 x 6" Woofer + 1" Tweeter</b> Wall In-fitted 2-Way Speaker 50W/4 Ohm, 89dB/1W/1m, 50Hz - 20kHz, 225x515x85mm	28,80	<b>34,60</b> EUR
	<b>CW-105B/4"</b> 2 way, 4" + 1" drivers, 15W (5/10/15W), 70/100V or 8 ohm, Sensitivity (1m, 1w) : 89 dB, Frequency Response : 80Hz-20kHz $\pm$ 3dB, 160x220x145mm, black	23,00	<b>28,00</b> EUR
	<b>CW-105W/4"</b> <b>NEW</b> 2 way, 4" + 1" drivers, 15W (5/10/15W), 70/100V or 8 ohm, Sensitivity (1m, 1w) : 89 dB, Frequency Response : 80Hz-20kHz $\pm$ 3dB, 160x220x145mm, white	23,00	<b>28,00</b> EUR
	<b>CW-105B/4"-4 Ohm</b> 20W, Voltage : 4 Ohm, Sensitivity (1m , 1w) : 89 dB, Frequency Response : 80Hz-20kHz $\pm$ 3dB, 170x215x150mm, black	20,00	<b>24,00</b> EUR
	<b>CW-105B/5"</b> 2 way, 5" + 1" drivers, 20W (5/10/20W), 70/100V or 8 ohm, Sensitivity (1m, 1w) : 90 dB, Frequency Response : 75Hz-20kHz $\pm$ 3dB, 185x245x162mm, black	31,00	<b>37,00</b> EUR
	<b>CW-105W/5"</b> <b>NEW</b> 2 way, 5" + 1" drivers, 20W (5/10/20W), 70/100V or 8 ohm, Sensitivity (1m, 1w) : 90 dB, Frequency Response : 75Hz-20kHz $\pm$ 3dB, 185x245x162mm, white	31,00	<b>37,00</b> EUR
	<b>CW-105B/6"</b> 2 way, 6" + 1" drivers, 30W (10/20/30W), 70/100V or 8 ohm, Sensitivity (1m, 1w) : 91 dB, Frequency Response : 70Hz-20kHz $\pm$ 3dB, 215x284x190mm, black	43,00	<b>52,00</b> EUR
	<b>CW-105B/6"-4 Ohm</b> 40W, Voltage : 4 Ohm, Sensitivity (1m , 1w) : 91 dB, Frequency Response : 75Hz-20kHz $\pm$ 3dB, black	40,00	<b>48,00</b> EUR
	<b>F41S</b> 2 Way, 4" + 1" drivers, 20W (2,5/5/10/20W), 100V, Sensitivity (1m , 1w) : 89 dB, 80Hz-20kHz $\pm$ 3dB, 170x215x150mm	23,00	<b>28,00</b> EUR
	<b>F51S</b> 2 Way, 5" + 1" drivers, 30W (3,75/7,5/15/30W), 100V, Sensitivity (1m , 1w) : 90 dB, 75Hz-20kHz $\pm$ 3dB, 182x242x162mm	31,00	<b>37,00</b> EUR
	<b>F61S</b> 2 Way, 6" + 1" drivers, 40W (5/10/20/40W), 100V, Sensitivity (1m , 1w) : 88 dB, 70Hz-20kHz, 215x190x284mm	43,00	<b>52,00</b> EUR




















ECPBR	Model	Description	EUR Netto (ex. VAT)	EUR + 20% DDS (incl. VAT)
<b>NEW</b>		<b>Soundwall 4.2</b> 2 Way - 40W, 4 Ohm, Sensitivity (1m , 1w) : 89 dB, 60Hz-17kHz Woofer: 2x 4" woofer. 19.45mm Voice Coil, 7 OZ 8 ohms. Compression Drive: 1.5 inch 13.24mm Voice Coil, 8 ohms. Finish: White/black ABS plastic white metal grille Dimensions (HxWxD): 305 x 225 x 170 mm, Weight Net: 3.9 kg	50,00	<b>60,00</b> EUR
		<b>W-3402</b> Wall Speaker 1.5/3/6W / 100V, 91dB/1W/1m, 200 Hz-16kHz, 87x228x173mm	9,00	<b>11,00</b> EUR
		<b>W-502T</b> Wall Speaker 6W (1.5/ 3/ 6W)/100V, 92dB/1W/1m, 130 Hz-17kHz, 160x267x80mm	13,00	<b>16,00</b> EUR
		<b>W-03</b> Wall Speaker 1,5; 3W/100V, 89dB/1W/1m, 400Hz - 10 kHz, <b>waterproof</b> , 120x120x60mm	6,00	<b>7,00</b> EUR
		<b>W-115</b> Wall Speaker 5; 10W/100V, 92dB/1W/1m, 150Hz - 17 kHz, 260x185x120mm	14,00	<b>17,00</b> EUR
		<b>L-650T</b> <b>6,5"</b> Rated Power: 2.5/5/10W /100V, Freq. response 50 Hz - 18 kHz, Sensitivity 92dB/1W/1m, Dimensions: Φ270x85mm	18,00	<b>21,60</b> EUR
		<b>H-5B</b> Pendent Speaker, Rated Power: 2.5/5/10W / 100V, Sensitivity (1m,1w): 92dB, Frequency Response:150HZ-15KHZ, Material: HIPS, φ180 mm 1.35 kg	17,00	<b>20,00</b> EUR
		<b>H-8A</b> Pendent Speaker, Rated Power: 5/10/20W / 100V, Sensitivity (1m,1w): 92±3dB, Frequency Response:80HZ-18KHZ, Material: ABS, φ254 mm 2.2 kg	35,00	<b>42,00</b> EUR
		<b>HS-69Q</b> Rated Power :30/45W, Line Voltage : 70/100V, Sensitivity (1m ,1w): 105 ±2dB, Frequency Response :12HZ-15KHZ, Material :ABS	65,00	<b>78,00</b> EUR
		<b>P-306</b> Sound Projector, Rated Power: 10W 100V, Sensitivity (1m,1w): 91±2dB, Frequency Response:130Hz-15kHz, Material: ABS φ138 mm x 205 mm, 1,6 kg Indoor Use	16,00	<b>19,00</b> EUR
		<b>TK-D206</b> Full Range Dual Direction Speaker 2 x 5", Rated Power: 10/20W, Line Voltage: 70/100V, Sensitivity (1m,1w): 94±2dB, Frequency Response:150HZ-14KHZ, Material: Aluminum Alloy, φ138 x 205 mm 2.8 kg, In/Outdoor use	35,00	<b>42,00</b> EUR
		<b>H-48</b> 2 Way Horn Speaker 50W (3,5/4,5/9/12,5/25/50W) /100V, 99dB/1W/1m, 90Hz- 20kHz, <b>waterproof</b> , 362x252x310mm	99,00	<b>119,00</b> EUR
		<b>S - 501</b> Rock speaker, 5-1/4" Coaxial Loudspeaker, 80 Hz - 16 kHz; 89 +/- 2 dB, 5/10/20 Watts 70-100V, Enclosure: Fiberglass Resin, 230 x 210 x 270 mm 3.5 kg	35,00	<b>42,00</b> EUR
		<b>G-3606</b> Garden speaker, 6,5"x1 & 2"x2 Loudspeakers, 100 Hz - 16 kHz; 87dB, Power Tab: 10/20/40 Watts, 100V, Enclosure: Fiberglass Resin, 320x250x380 mm 5 kg	37,00	<b>44,00</b> EUR
		<b>G-20</b> Garden speaker, 4" Loudspeaker, 80 Hz - 15 kHz; 85dB, Power Tab: 10/20 Watts, 100V, Enclosure: ABS, Φ215 x 245 mm, 2.1 kg	39,00	<b>47,00</b> EUR
		<b>H-3306</b> High Power, Two-Way Horn Speaker, Rated Power: 100W / 100V, Sensitivity: 108dB/1W/1m, Frequency Response: 70Hz-18KHz Dimensions: 610x1040x760 mm, Weight: 45 kg Enclosure: FRP, IP66,	700,00	<b>840,00</b> EUR

<i>ECPBR</i>	<i>Model</i>	<i>Description</i>	<i>EUR Netto (ex. VAT)</i>	<i>EUR + 20% DDS (incl. VAT)</i>
<b>ELA MIXER &amp; PREAMPLIFIERS</b>				
	<b>AP-9811P</b>	Mixer pre-amplifier with five microphone, three auxiliary, and two priority inputs. Features include separate bass, treble and input gain controls.	96,00	<b>115,00</b> EUR
<b>ELA MIXER-AMPLIFIERS 100V</b>				
	<b>AP-200P V2</b>	70W RMS, 3 MIC, 2 AUX inputs, MIC1 Priority Mute, 1 LINE-OUT, 4-16 ohm / 70 V / 100 V outputs, Bass, treble, individual & master volume controls	97,00	<b>116,00</b> EUR
	<b>AP-300P V2</b>	130W RMS, 3 MIC, 2 AUX inputs, MIC1 Priority Mute, 1 LINE-OUT, 4-16 ohm / 70 V / 100 V outputs, Bass, treble, individual & master volume controls	134,00	<b>161,00</b> EUR
	<b>AP-600P V2</b>	260W RMS, 3 MIC, 2 AUX inputs, MIC1 Priority Mute, 1 LINE-OUT, 4-16 ohm / 70 V / 100 V outputs, Bass, treble, individual & master volume controls	191,00	<b>229,00</b> EUR
	<b>AP-1000P V2</b>	360W RMS, 3 MIC, 2 AUX inputs, MIC1 Priority Mute, 1 LINE-OUT, 4-16 ohm / 70 V / 100 V outputs, Bass, treble, individual & master volume controls	288,00	<b>346,00</b> EUR
	<b>PB-310P</b>	Mixer amplifier 120W RMS, 2 MIC, 3 AUX inputs, MIC 1 Priority, 6 outputs with individual volume control, 1 LINE-OUT, 4-16 ohm OUT	171,00	<b>205,00</b> EUR
<b>NEW</b> 	<b>MX-60T</b>	60W RMS Compact Amplifier with USB MP3 player & AM/FM tuner, 4-8-16 Ohm / 70 / 100V out Telephone Paging/MIC1 Input; MIC2 input, AUX/CD input; Bass, Middle & Treble tone controls; Individual Volume Controls; Dimensions (WxHxD): 270x90x260 mm, Weight: 4.7 kg	148,00	<b>177,60</b> EUR
<b>NEW</b> 	<b>AP-200M</b>	70W RMS, 3 MIC, 2 AUX inputs, MIC1 Priority Mute, 1 LINE-OUT, 4-16 ohm / 70V / 100V out, bass, treble, individual volume controls, 4-tone chime, AM/FM Tuner, USB MP3 player	148,00	<b>178,00</b> EUR
<b>NEW</b> 	<b>AP-300M</b>	130W RMS, 3 MIC, 2 AUX inputs, MIC1 Priority Mute, 1 LINE-OUT, 4-16 ohm / 70V / 100V out, bass, treble, individual volume controls, 4-tone chime, AM/FM Tuner, USB MP3 player	181,00	<b>217,00</b> EUR
<b>NEW</b> 	<b>AP-600M</b>	260W RMS, 3 MIC, 2 AUX inputs, MIC1 Priority Mute, 1 LINE-OUT, 4-16 ohm / 70V / 100V out, bass, treble, individual volume controls, 4-tone chime, AM/FM Tuner, USB MP3 player	258,00	<b>310,00</b> EUR
<b>ELA POWER AMPLIFIERS 100V</b>				
	<b>PAM120</b>	120W RMS, 100 V; Gain control -12 to 0 dB; 60Hz-20kHz +/-3dB; S/N >90dB; Power requirements: 220-240V AC, 50/60Hz; 24V DC; 19" 3U Height; Weight 13 kg	177,00	<b>212,00</b> EUR
	<b>PAM240</b>	240W RMS, 100 V; Gain control -12 to 0 dB; 60Hz-20kHz +/-3dB; S/N >90dB; Power requirements: 220-240V AC, 50/60Hz; 24V DC; 19" 3U Height; Weight 17,66 kg	215,00	<b>258,00</b> EUR
	<b>PAM360</b>	360W RMS, 100 V; Gain control -12 to 0 dB; 60Hz-20kHz +/-3dB; S/N >90dB; Power requirements: 220-240V AC, 50/60Hz; 24V DC; 19" 3U Height; Weight 20,8 kg	255,00	<b>306,00</b> EUR
	<b>AP-1500</b>	360W RMS, Balanced Inputs, 4-16 ohm / 70 V / 100 V outputs, extensive protection	243,00	<b>292,00</b> EUR
	<b>AP-2500</b>	660W RMS, Balanced Inputs, 4-16 ohm / 70 V / 100 V outputs, extensive protection	470,00	<b>564,00</b> EUR
<b>ELA SYSTEMS COMPONENTS</b>				
	<b>AP-9812M</b>	10 monitoring channels, 5 LED level meter; internal speaker, Volume control	91,00	<b>109,00</b> EUR
	<b>AP-9810P</b>	10-zone paging selector. Versatile paging selector that has 10 channels, 10 alarm inputs / activation outputs, remote control connection for the remote paging station, 2 microphone, 2 line inputs, built-in chime generator, and priority mute function. Up to 4 paging selectors can be linked to provide for additional paging zones - 20, 30, or 40!	100,00	<b>120,00</b> EUR
	<b>DCI-10R</b>	10-Zone Remote Paging Station for use with AP-9810P. Remotely controls the paging selector at a distance of up to 1 km! Additional paging stations can be linked together to provide for up to four remote paging areas.	90,00	<b>108,00</b> EUR
	<b>AP-9813B</b>	10-Zone Front panel speaker zone selector. Selects up to 10 speaker zones and provides 2 normal amplifier inputs. With two amplifier inputs, A and B, it can be used as two separate 5-zone selectors (2 x 5 zones) or as a single 10-zone (1 x 10 zones) selector.	100,00	<b>120,00</b> EUR
	<b>AP-9813D</b>	10-Zone Front panel speaker zone selector with Alarm In/Out, 2 amplifier line Inputs - one input for a normal (background music) amplifier, the other for a priority (paging, emergency) amplifier. It automatically switches from the background music amplifier to the priority amplifier for any of 10 channel inputs. This feature is useful for zone paging and emergency notification.	113,00	<b>136,00</b> EUR
	<b>AP-9815E V2</b>	Emergency Panel / Alarm Annunciator, Triggered by alarm signals, this emergency panel and alarm annunciator outputs a warning siren or user-recorded urgent announcement or siren. Either automatically or manually controlled, it's simple for the user to record an announcement with the built-in 60-second digital IC. Features "FIRE" button to immediately broadcast the siren or emergency announcement.	175,00	<b>210,00</b> EUR
	<b>AP-9848S</b>	4 x 8 Audio Matrix, Multi-channel sound source (CD player, AM/FM tuner) input/output selector that provides 4 sound source inputs and 8 audio outputs. Each output channel can select from any of the four inputs. In case of alarm, the emergency signal can automatically cut over the four sound source inputs.	178,00	<b>214,00</b> EUR
	<b>AP-9881J</b>	Programm Player, Contains an entire series of melodies and chimes to be played at programmed times. Simultaneous manual / fixed time automatic broadcast with a repetitive cycle. LCD display and jog dial for easy program setting. Music/Message event management, 40 power-on and power-off time points, Controls up to 6 external program sources	304,00	<b>365,00</b> EUR
	<b>AP-9820S</b>	24VDC Switching Power Supply. 10-channel switching power supply for use in a public address system to forcefully insert 24VDC over the system to provide power for sirens and other emergency reporting equipment. Activated by a 10-channel input, the input alarm signals control the 24V power source outputs.	117,00	<b>140,00</b> EUR
	<b>DCI-26C</b>	Volume Control. With three inputs and three outputs, the DCI-26C is a master volume control that bypasses zone volume controls giving a greater degree of volume control in the selected zones.	142,00	<b>170,00</b> EUR

Model	Description	EUR Netto (ex. VAT)	EUR + 20% DDS (incl. VAT)
<b>Honeywell</b>			
<b>HONEYWELL X-618 Digital EN-54 PA/VA Syst</b>			
 <b>X-DCS2000/EN</b>	<b>EN54-24 certified X-618 Digital Integrated System Manager</b> 8 Zones, Multi-Functional Integration, without PTT microphone Line Fault Detection; Monitoring; Self-test; Sound Volume Control; Automatic Volume Control Power Amplifier Management; Voice Information Management; Business & Emergency Paging; 100-240 VAC & 24 VDC power supply; Dimensions (WxHxD): 483x88x420mm, 2U; 9.3 kg.	1.459,00	<b>1.751,00</b> EUR
 <b>HN-PTT</b>	Optional Push-to-talk Microphone (Compatible with X-DCS2000/EN) Dynamic, Hyper cardioid; Impedance 500Ω±30% at 1KHz; Frequency Response 50Hz~15KHz; Sensitivity 0°-77dB±3dB, Weight 30g	52,00	<b>62,00</b> EUR
 <b>X-DA1500EN</b>	<b>EN54-24 certified X-618 system power amplifier</b> High Efficiency Class D Power Amplifier, 1x2500W, 100V/70 Output, Input 1.414VRMS, 20kΩ, S/N Ratio >100dB; THD <0.05% @ 1/3 rated power; 100-240 VAC & 24 VDC power supply; Dimensions (WxHxD): 483x88x416mm, 2U; 11.3 kg.	795,00	<b>954,00</b> EUR
 <b>X-DA2250EN</b>	<b>EN54-24 certified X-618 system power amplifier</b> High Efficiency Class D Power Amplifier, 2x2500W, 100V/70 Output; Input 1.414VRMS, 20kΩ, S/N Ratio >100dB; THD <0.05% @ 1/3 rated power; 100-240 VAC & 24 VDC power supply; Dimensions (WxHxD): 483x88x416mm, 2U; 12.2 kg.	964,00	<b>1.157,00</b> EUR
 <b>X-DA4125EN</b>	<b>EN54-24 certified X-618 system power amplifier</b> High Efficiency Class D Power Amplifier, 4x1250W, 100V/70 Output; Input 1.414VRMS, 20kΩ, S/N Ratio >100dB; THD <0.05% @ 1/3 rated power; 100-240 VAC & 24 VDC power supply; Dimensions (WxHxD): 483x88x416mm, 2U; 12.9 kg.	1.209,00	<b>1.451,00</b> EUR
 <b>X-NPMI</b>	<b>EN54-24 certified X-618 Configurable Network Paging Console</b> 4.3" Color Touch Screen; Intuitive and simple user interface; Detachable gooseneck microphone; Built-in monitor loudspeaker for broadcast monitoring & intercom; Digital audio processing; suitable for desktop flush mount; Dimensions (WxHxD): 210x55x110mm	468,00	<b>562,00</b> EUR
 <b>X-NR/EN</b>	<b>EN54-24 Network Resource Interface</b> 4 channels network audio source; 4 AUX input ports, 4 balance input ports with Phantom 32 dry contacts in and 8 try contacts out; built-in 4GB SD card for storing audio files; 4 ports 10M/100MB Ethernet switch; Power: AC 100~240V, 50/60Hz; 24V DC Dimensions (WxHxD): 482x88x420mm, 2U; 7.3 kg.	1.888,00	<b>2.266,00</b> EUR
 <b>X-MAP4</b>	<b>All-in-1 Audio Source Unit CD/MP3/FM/DAB</b> CD slot, SD card slot, USB slot, DAB/FM aerial terminal; 2 separate stereo out 2 sources simultaneous play; RS485 Protocol Interface Dimensions (WxHxD): 482x44x252mm, 1U, white (RAL9003)	254,00	<b>305,00</b> EUR
 <b>HN-D32N</b>	<b>Noise detector in Speaker Design</b> Transmission Distance up to 200 Meters; Directivity: Cardioid; Frequency Range 60Hz-18kHz; Max SPL 152dB; Sensitivity 2.4 mV; Impedance 2 kΩ Dimensions: Φ 200x118mm; Mounting hole: Φ140mm; white (RAL9010)	115,00	<b>138,00</b> EUR
 <b>X-SPT900</b>	<b>X-SMART Med to Small Project System Management Software Package</b> (Include 1 sever and 1 client interface) Load & operation on E-maps; 3 layers maps display; Monitoring of all devices in the system. Fault alarms activation; Error locations display; Administrator can add/remove users and configure access controls; Supports Text-to-Speech (TTS) function; Broadcast audio files saved on the server in any zone within the system network	1.131,00	<b>1.357,00</b> EUR
<b>Honeywell</b>			
<b>HONEYWELL EN 54-24 LOUDSPEAKERS</b>			
 <b>L-VCM6B/EN (C)</b>	<b>EN54-24 certified ceiling speaker with steel fire dome</b> 5" driver, steel body & front grille, ceramic input terminal with thermal fuse, DC blocking capacitor Rated power 0.75/1.5/3/6W 100 V; Frequency Response 180Hz-20kHz; Sensitivity 91dB/1W/1m (100Hz-10kHz); Dimensions: Φ180x129mm, Mounting hole: Φ155mm, 1.29kg, white grille (RAL9010), red	28,00	<b>34,00</b> EUR
 <b>L-VCM6A/EN (C)</b>	<b>EN54-24 certified ceiling speaker with steel fire dome</b> 6.5" driver, steel body & front grille, ceramic input terminal with thermal fuse, DC blocking capacitor Rated power 0.75/1.5/3/6W 100 V; Frequency Response 170Hz-20kHz; Sensitivity 91dB/1W/1m (100Hz-10kHz); Dimensions: Φ222x129mm, Mounting hole: Φ195mm, 1.57 kg, white grille (RAL9003), red	33,00	<b>40,00</b> EUR
 <b>L-VVM06A/EN (C)</b>	<b>EN54-24 certified steel cabinet wall speaker</b> 4" driver, steel body and front grille, ceramic input terminal with thermal fuse, DC blocking capacitor Rated power 0.75/1.5/3/6W 100 V; Frequency Response 300Hz-15kHz; Sensitivity 91dB/1W/1m (100Hz-10kHz); Dimensions (WxHxD): 170x170x63mm, 1.56 kg, white (RAL9003)	37,00	<b>44,00</b> EUR
 <b>L-VJM10A/EN (C)</b>	<b>EN54-24 certified sound projector</b> aluminium body, ceramic input terminal with thermal fuse, DC blocking capacitor Rated power 1.25/2.5/5/10W 100 V; Frequency Response 150Hz-20kHz; Sensitivity 90dB/1W/1m (100Hz-10kHz); Dimensions: Φ140 x D195mm, 2.62 kg, white (RAL9003), IP65	66,00	<b>79,00</b> EUR
 <b>L-VJM20A/EN (C)</b>	<b>EN54-24 certified sound projector</b> aluminium body, ceramic input terminal with thermal fuse, DC blocking capacitor Rated power 2.5/5/10/20W 100 V; Frequency Response 150Hz-20kHz; Sensitivity 90dB/1W/1m (100Hz-10kHz); Dimensions: Φ140 x D195mm, 2.65 kg, white (RAL9003), IP65	69,00	<b>83,00</b> EUR
 <b>L-VBM20A/EN (C)</b>	<b>EN54-24 certified bi-directional sound projector</b> aluminium body, ceramic input terminal with thermal fuse, DC blocking capacitor Rated power 2.5/5/10/20W 100 V; Frequency Response 150Hz-15kHz; Sensitivity 87dB/1W/1m (100Hz-10kHz); Dimensions: Φ140 x D195mm, 3.23 kg, white (RAL9003), IP65	98,00	<b>118,00</b> EUR
 <b>L-VOM20A/EN (C)</b>	<b>EN54-24 certified outdoor column loudspeaker</b> 2x4" drivers aluminium body, ceramic input terminal with thermal fuse, DC blocking capacitor Rated power 5/10/20/40W 100 V; Frequency Response 300Hz-15kHz; Sensitivity 92dB/1W/1m (100Hz-10kHz); Dimensions (WxHxD): 165x344x150mm, 3.75kg, white (RAL9003), IP66	146,00	<b>175,00</b> EUR
 <b>L-VOM40A/EN (C)</b>	<b>EN54-24 certified outdoor column loudspeaker</b> 4x4" drivers aluminium body, ceramic input terminal with thermal fuse, DC blocking capacitor Rated power 2.5/5/10/20W 100 V; Frequency Response 300Hz-15kHz; Sensitivity 94dB/1W/1m (100Hz-10kHz); Dimensions (WxHxD): 165x568x150mm, 5.75kg, white (RAL9003), IP66	189,00	<b>227,00</b> EUR

EC P B R	Model	Description	EUR Netto (ex. VAT)	EUR + 20% DDS (incl. VAT)
<b>DESKTOP MICROPHONES</b>				
	<b>MC-200</b>	2 tones chime, ON/OFF switch, Desktop stand	37,00	<b>44,00</b> EUR
	<b>ED-15</b>	ON/OFF switch, Flexible gooseneck stem, Desktop stand	24,00	<b>29,00</b> EUR
	<b>ED-A94</b>	Condenser, cardioid, ON/OFF switch, Flexible gooseneck stem, Desktop stand	36,00	<b>43,00</b> EUR
	<b>DD-A91</b>	Dynamic, cardioid, PTT switch, Flexible gooseneck stem, Desktop stand	45,00	<b>54,00</b> EUR

## VOLUME CONTROLS




















	<b>VE-505</b>	5W / 100V Volume control, 11-step volume level rotary knob, (without emergency input)	3,30	<b>4,00</b> EUR
	<b>VE-530</b>	30W / 100V Volume control, 11-step volume level rotary knob, (without emergency input)	5,00	<b>6,00</b> EUR
	<b>VE-560</b>	60W / 100V Volume control, 11-step volume level rotary knob, (without emergency input)	9,00	<b>10,80</b> EUR
	<b>VE-560D</b>	60W / 100V Volume control, 11-step volume level rotary knob, <b>D - indicates override relay 24 V</b>	10,00	<b>12,00</b> EUR
	<b>VE-5120D</b>	120W / 100V Volume control, 11-step volume level rotary knob, <b>D - indicates override relay 24 V</b>	15,00	<b>18,00</b> EUR
	<b>V-605D</b>	5W / 100V Volume control + 5 ch. program selector, 5-step volume level rotary knob, <b>D - indicates override relay 24 V</b>	11,00	<b>13,20</b> EUR
	<b>V-630D</b>	30W / 100V Volume control + 5 ch. program selector, 5-step volume level rotary knob, <b>D - indicates override relay 24 V</b>	12,00	<b>14,40</b> EUR
	<b>V-660D</b>	60W / 100V Volume control + 5 ch. program selector, 5-step volume level rotary knob, <b>D - indicates override relay 24 V</b>	13,00	<b>15,60</b> EUR
	<b>V-6120D</b>	120W / 100V Volume control + 5 ch. program selector, 5-step volume level rotary knob, <b>D - indicates override relay 24 V</b>	17,00	<b>20,40</b> EUR
<b>NEW</b>	<b>V-knob</b>	Knob for V-series volume controls	0,40	<b>0,50</b> EUR
	<b>VE-CC</b>	Console 76x76x42 for the V and VE-Series	0,40	<b>0,50</b> EUR
	<b>UV-306D</b>	Volume control, 6W/100V, Total attenuation 33 dB, <b>Attenuation positions 10+ off, Priority relay 24V</b> , Dimensions 80x80x48 mm	6,00	<b>7,20</b> EUR
	<b>UV-312D</b>	Volume control, 12 W/100V, Total attenuation 33 dB, <b>Attenuation positions 10+ off, Priority relay 24V</b> , Dimensions 80x80x48 mm	11,00	<b>13,20</b> EUR
	<b>UV-336D</b>	Volume control, 36 W/100V, Total attenuation 33 dB, <b>Attenuation positions 10+ off, Priority relay 24V</b> , Dimensions 80x80x48 mm	15,00	<b>18,00</b> EUR
	<b>UV-350D</b>	Volume control, 50W/100V, Total attenuation 33 dB, <b>Attenuation positions 10+ off, Priority relay 24V</b> , Dimensions 80x80x48 mm	21,00	<b>25,20</b> EUR
	<b>UV-325S</b>	Volume control 2x25W / 4Ohm, Total attenuation 30 dB, <b>Attenuation positions 10 + off</b> , Dimensions 80x80x46	23,00	<b>27,60</b> EUR
	<b>EU-601D</b>	Program selector, 6 steps program selection, <b>Priority relay 24V</b> , Dimensions: 80x80x28mm	6,00	<b>7,20</b> EUR
*** For EU & UV Series use standard round installation consoles				
	<b>V-8120K</b>	Volume control, 120W/100V, Total attenuation 33 dB, Attenuation positions 10+ off, <b>Priority relay 24V</b> , Dimensions 115x70x85 mm	18,00	<b>21,60</b> EUR








## Honeywell

## HONEYWELL VOLUME CONTROLS
















<b>NEW</b>	<b>HN-VC06</b>	6W Volume controller, 3/4 wire, ABS Material, with 24V Override Function Attenuation 5 × 2 dB + off; Dimensions (L×W×D): 86 × 86 × 52.5 mm, white (RAL 9010)	15,00	<b>18,00</b> EUR
<b>NEW</b>	<b>HN-VC30</b>	30W Volume controller, 3/4 wire, ABS Material, with 24V Override Function Attenuation 5 × 2 dB + off; Dimensions (L×W×D): 86×86×67.5 mm, white (RAL 9010)	18,00	<b>22,00</b> EUR
<b>NEW</b>	<b>HN-VC60</b>	60W Volume controller, 3/4 wire, ABS Material, with 24V Override Function Attenuation 5 × 2 dB + off; Dimensions (L×W×D): 86×86×75.5 mm, white (RAL 9010)	24,00	<b>29,00</b> EUR
<b>NEW</b>	<b>HN-VC120</b>	120W Volume controller, 3/4 wire, ABS Material, with 24V Override Function Attenuation 5 × 2 dB + off; Dimensions (L×W×D): 86×86×75.5 mm, white (RAL 9010)	33,00	<b>40,00</b> EUR
































































EC P B R	Model	Description	EUR Netto (ex. VAT)	EUR + 20% DDS (incl. VAT)
<b>RACK SYSTEM</b>				
	<b>APR - 10</b>	19" rack - 10 U incl. Fan Module and Power Distribution	150,00	<b>180,00</b> EUR
	<b>APR - 16U</b>	19" rack - 16 U incl. Fan Module and Power Distribution, 61 x 61 x 80 cm	275,00	<b>330,00</b> EUR
	<b>APR - 27U</b>	19" rack - 24U incl. Fan Module and Power Distribution, 61 x 61 x 120 cm 52 kg	350,00	<b>420,00</b> EUR
	<b>APR - 42U</b>	19" rack - 37U incl. Fan Module and Power Distribution, 61 x 61 x 180 cm 66 kg	425,00	<b>510,00</b> EUR
<b>Accessories</b>				
	<b>TR 40W/100V</b>	Speaker Transformer 100V / 8Ohm, 40W / 20W / 10W	5,00	<b>6,00</b> EUR
	<b>TR 240</b>	Output Transformer 4Ohm to 100V / 70V / 25V, 240W	29,00	<b>34,80</b> EUR
	<b>CTB</b>	3-pole ceramic terminal block	1,00	<b>1,20</b> EUR
	<b>KP560 HED</b>	<b>Wall mount heavy duty steel tube speaker stand</b> The mounting bracket allows both horizontal and vertical adjustment. Load capacity: 35 kg Pipe dimension : 25 x 25 x 1 mm 35 x 15 mm, Arm length : 390 mm , Colour : Matte black	10,00	<b>12,00</b> EUR
	<b>FRE300-HED</b>	<b>Speaker stand</b> Load capacity: 80 kg Length: 1250-2200mm Colour : Matte black	19,00	<b>22,80</b> EUR
<b>Connectors</b>				
	<b>NC-3FX-HED</b>	3 pole XLR female cable connector with Nickel housing and silver contacts.	1,00	<b>1,20</b> EUR
	<b>NC-3MX-HED</b>	3 pole XLR male cable connector with Nickel housing and silver contacts.	1,00	<b>1,20</b> EUR
	<b>XLR3FV HED</b>	3 pole XLR female cable connector with Nickel housing and silver contacts.	0,64	<b>0,77</b> EUR
	<b>XLR3MV HED</b>	3 pole XLR male cable connector with Nickel housing and silver contacts.	0,64	<b>0,77</b> EUR
	<b>XLR3MDL HED</b>	3 pole XLR male panel connector with Nickel housing and silver contacts.	0,43	<b>0,52</b> EUR
	<b>MINI3MP HED</b>	3 pole Mini XLR male cable connector with Nickel housing and silver contacts.	1,92	<b>2,30</b> EUR
	<b>MINI3FV HED</b>	3 pole Mini XLR female cable connector with Nickel housing and silver contacts.	1,92	<b>2,30</b> EUR
	<b>MRCA25 RD HED</b> <b>MRCA25 WH HED</b>	RCA (Chinch) Connector with gold contacts / red or white /	0,51	<b>0,61</b> EUR
	<b>S2C HED</b>	2 pole Phono Jack cable connector with Nickel housing and silver / gold contacts.	0,64	<b>0,77</b> EUR
	<b>NP2X HED</b> <b>(LC3134)</b>	Mono 1/4" professional phone plug, 2 pole, nickel contacts, nickel housing	0,64	<b>1,00</b> EUR
	<b>NP3 HED</b> <b>(LC3135)</b>	Stereo 1/4" professional phone plug, 3 pole, nickel contacts, nickel housing, I257 Professional phone plug with robust metal shell and chuck type strain relief. et	0,85	<b>1,00</b> EUR
	<b>HT Mono Jack</b>	2 pole Phono Jack cable connector with Nickel / Plastic housing	0,42	<b>0,50</b> EUR
	<b>HT Stereo Jack</b>	3 pole Phono Stereo Jack cable connector with Nickel / Plastic housing	0,42	<b>0,50</b> EUR

<i>ECPBR</i>	<i>Model</i>	<i>Description</i>	<i>EUR Netto (ex. VAT)</i>	<i>EUR + 20% DDS (incl. VAT)</i>
	<b>HT Mono Jack Big</b>	2 pole Phono Jack cable connector with Nickel / Plastic housing and cable spring	0,42	<b>0,50</b> EUR
	<b>HT Stereo Jack Big</b>	3 pole Phono Stereo Jack cable connector with Nickel / Plastic housing and cable spring	0,42	<b>0,50</b> EUR
	<b>NL2FC HED</b>	2 pole speaker cable connector, quick lock, integrated chuck type strain relief for cables 6 - 10 mm diameter, intermates with 4-pole chassis connector and makes contact with +1/-1	1,07	<b>1,28</b> EUR
	<b>NL4FC HED</b>	4 pole speaker cable connector, quick lock, integrated chuck type strain relief for cables 6 - 10 mm diameter, makes contact with +1/-1 and +2/-2	1,28	<b>1,54</b> EUR
	<b>NL4MP HED</b>	4 pole speaker chassis connector, black D-size flange, countersunk thru holes, 3/16" flat tabs	0,64	<b>0,77</b> EUR
	<b>NL4MPR HED</b>	4 pole speaker chassis connector, black round G-size flange, countersunk thru holes, 3/16" flat tabs	0,85	<b>1,02</b> EUR
	<b>HT BANANA</b>	Dual Banana Plug Connector designed to terminate speaker cables for DJ and pro-audio and consumer applications. Feature screw-tite terminals and click-tite strain relief for easy termination.	0,43	<b>0,52</b> EUR

## Connection adapters & Couplers

	<b>AT340 (LB2001)</b>	Professional metal adapter : 3-pole XLR female socket -> 3-pole XLR female socket	1,49	<b>1,79</b> EUR
	<b>AT330 (LB2002)</b>	Professional metal adapter : 3-pole XLR male socket -> 3-pole XLR male socket	1,49	<b>1,79</b> EUR
	<b>AT355DMX (LB2003-1)</b>	Professional metal adapter for DMX cables: XLR 5-pole female socket -> XLR 3-pole male plug.	1,49	<b>1,79</b> EUR
	<b>AT350DMX (LB2003-2)</b>	Professional metal adapter for DMX cables: XLR 3-pole female socket -> XLR 5-pole male plug.	1,49	<b>1,79</b> EUR
	<b>AT295F (LB2004)</b>	Professional metal adapter XLR 3-pole female socket -> 1/4" female jack.	1,49	<b>1,79</b> EUR
	<b>AT305F (LB2005)</b>	Professional metal adapter XLR 3-pole male socket -> 1/4" female jack.	1,49	<b>1,79</b> EUR
	<b>AT295 (LB2016)</b>	Professional metal adapter XLR 3-pole female socket -> 1/4" male stereo jack.	1,49	<b>1,79</b> EUR
	<b>AT305 (LB2017)</b>	Professional metal adapter XLR 3-pole male socket -> 1/4" male stereo jack.	1,49	<b>1,79</b> EUR
	<b>AT520 (LB2057)</b>	Professional metal adapter: 3-pole XLR female socket -> RCA female socket.	1,49	<b>1,79</b> EUR
	<b>AT510 (LB2058)</b>	Professional metal adapter: 3-pole XLR female socket -> RCA male plug.	1,49	<b>1,79</b> EUR
	<b>AT500 (LB2059)</b>	Professional metal adapter: 3-pole XLR female socket -> RCA female socket.	1,49	<b>1,79</b> EUR
	<b>AT530 (LB2060)</b>	Professional metal adapter: 3-pole XLR male plug -> RCA male plug.	1,49	<b>1,79</b> EUR
	<b>AT625 (LB2019)</b>	Professional metal adapter: 6.3 mm. stereo jack female socket with security lock -> 3-pole XLR female socket.	1,49	<b>1,79</b> EUR
	<b>AT615 (LB2019-1)</b>	Professional metal adapter: 6.3 mm. stereo jack female socket with security lock -> 6.3 mm. stereo jack female socket with security lock.	1,49	<b>1,79</b> EUR
	<b>AT635 (LB2020)</b>	Professional metal adapter: 6.3 mm. stereo jack female socket with security lock -> 6.3 mm. stereo jack female socket with security lock.	1,49	<b>1,79</b> EUR

ECPBR	Model	Description	EUR Netto (ex. VAT)	EUR + 20% DDS (incl. VAT)
 	<b>SPK8MM (LB2027)</b>	8 pole speakON coupler	1,49	<b>1,79</b> EUR
 	<b>AT190 Gold (LB2029)</b>	Professional metal gold plated adapter: RCA female socket -> 6.3 mm. mono jack male plug.	0,85	<b>1,02</b> EUR
 	<b>AT165 Gold (LB2054)</b>	Professional metal gold plated adapter: 3.5 stereo jack female socket -> 6.3 mm. stereo jack male plug.	1,28	<b>1,54</b> EUR
 	<b>AT190 (LB2030)</b>	ABS adapter: RCA female socket -> 6.3 mm. mono jack male plug.	0,26	<b>0,31</b> EUR
 	<b>AT165 (LB2034)</b>	ABS adapter: 3.5 stereo jack female socket -> 6.3 mm. stereo jack male plug.	0,43	<b>0,52</b> EUR
 	<b>AT120 (LB2036)</b>	ABS adapter: 6.3 mm. stereo jack female socket ->3.5 mm. stereo jack male plug.	0,43	<b>0,52</b> EUR
 	<b>AT128 (LB2044)</b>	ABS adapter: 6.3 mm. stereo jack female socket ->3.5 mm. stereo jack male plug.	0,48	<b>0,58</b> EUR
 	<b>AT250Y (LB2048)</b>	ABS "Y" adapter: 2 RCA female sockets -> 6.3 mm. stereo jack male plug.	0,58	<b>0,70</b> EUR
 	<b>Terminal Plate LF6055 (Soundking AJ117)</b>	speakON Binding Post. Inox plate. 2 pole chassis speakON type female conector INOX plate: 87.2 x 87.2 mm	1,88	<b>2,26</b> EUR
 	<b>Terminal Plate LF6058</b>	Dual XLR-F Binding Post, Inox plate 2 x XLR - F chassis connectors with Solder cups Inox plate: 87.2 X 87.2 mm.	2,71	<b>3,25</b> EUR
 	<b>Terminal Plate LF6059</b>	Stereo RCA Binding Post - 2 x female, gold plated RCA connectors, Black and Red - Solder cups - Inox plate: 87.2 x 87.2 mm.	2,27	<b>2,72</b> EUR
 	<b>Terminal Plate LF6072</b>	Combi composite and HDMI Binding Post - Composite video, gold plated RCA female connector - Audio L+R gold plated RCA female connectors - HDMI coupler connector - Inox plate: 87.2 x 87.2 mm	6,73	<b>8,08</b> EUR
<b>Ready Made Cables</b>				
 	<b>CAB-USB2.0 AM/BM-1.5M</b>	24AWG USB2.0 AM-Mini USB 4P, 1,5 m	1,30	<b>1,56</b> EUR
 	<b>CAB-USB3.0 AM/AF-1.5M</b>	24AWG USB 3.0 A MALE-A FEMALE 1,5 m	3,00	<b>3,60</b> EUR
 	<b>CAB-USB3.0 AM/BM-1.5M</b>	24AWG USB3.0 AM-BM, 1,5 m	3,00	<b>3,60</b> EUR
 	<b>HDMI90/HDMI90-1.5M GOLD</b>	HDMI 90° Gold / HDMI 90° Gold plated connectors - 1,5 m	4,30	<b>5,16</b> EUR
 	<b>HDMI90/HDMI90-3M GOLD</b>	HDMI 90° Gold / HDMI 90° Gold plated connectors - 3 m	4,90	<b>5,88</b> EUR
 	<b>HDMI/HDMI-1.5M GOLD-BL</b>	HDMI/HDMI-1.5M GOLD Plated, Black	5,30	<b>6,36</b> EUR
 	<b>HDMI/HDMI-3M GOLD-BL</b>	HDMI/HDMI-3.0M GOLD Plated, Black	7,10	<b>8,52</b> EUR
 	<b>CAB-XLR/XLR-1M (B)</b>	Microphone / Line XLR / XLR Cable 1.0 m XLR male / XLR female	2,00	<b>2,40</b> EUR
 	<b>CAB-XLR/XLR-2.5M (B)</b>	Microphone / Line XLR / XLR Cable 2.5 m XLR male / XLR female	3,00	<b>3,60</b> EUR
 	<b>CAB-XLR/XLR-5M (B)</b>	Microphone / Line XLR / XLR Cable 5 m XLR male / XLR female	4,00	<b>4,80</b> EUR
	<b>HT XLR3FV / M.Jack L6</b>	Microphone / XLR Cable 6 m Mono Jack / XLR female	0,85	<b>1,02</b> EUR
	<b>HT 2xJack / 2xJack L1.5</b>	Instruments Cable 2x Mono Jack / 2x Mono Jack 1.5 m 2x Mono Jack 6,3mm - 2x Mono Jack 6,3mm 0.12*20+0.12*64+ , Conductive PVC, Color:Black	0,85	<b>1,02</b> EUR
	<b>HT 2xJack / 2xJack L3</b>	Instruments Cable 2x Mono Jac / 2x Mono Jac 3 m 2x Mono Jack 6,3mm - 2x Mono Jack 6,3mm 0.12*20+0.12*64+ , Conductive PVC, Color:Black	0,85	<b>1,02</b> EUR

ECPBR	Model	Description		EUR Netto (ex. VAT)	EUR + 20% DDS (incl. VAT)
	<b>HT Jack / Jack 6</b>	<b>Instruments Cable Jack / Jack 6 m</b> Mono Jack 6,3mm - Mono Jack 6,3mm 0.12*20+0.12*64+ , Conductive PVC, Color:Black	6 meter	0,85	<b>1,02</b> EUR
	<b>HT Jack / Jack L10</b>	<b>Instruments Cable Jack / Jack 10 m</b> Mono Jack 6,3mm - Mono Jack 6,3mm 0.12*20+0.12*64+ , Conductive PVC, Color:Black	10 meter	0,85	<b>1,02</b> EUR
<b>NEW</b>		<b>Instruments Cable Jack / Jack 3 m</b> Mono Jack 6,3mm - Mono Jack 6,3mm 0.12*20+0.12*64+ , Conductive PVC, Color:Black	3 meters	2,98	<b>3,58</b> EUR
<b>NEW</b>	<b>CAB-JMO/JMO-6M (B)</b>	<b>Instruments Cable Jack / Jack 6 m</b> Mono Jack 6,3mm - Mono Jack 6,3mm 0.12*20+0.12*64+ , Conductive PVC, Color:Black	6 meters	5,10	<b>6,12</b> EUR
<b>NEW</b>		<b>Instruments Cable Jack 90° / Jack 90° 3 m</b> Right Angle Mono Jack 6,3mm - Mono Jack 6,3mm	3 meter	3,80	<b>4,56</b> EUR
<b>NEW</b>		<b>Instruments Cable Jack 90° / Jack 6.0 m</b> Right Angle Mono Jack 6,3mm - Mono Jack 6,3mm	6 meter	5,10	<b>6,12</b> EUR
	<b>HT Jack / Jack 90 GL1,5</b>	<b>Instruments Cable Jack 90° / Jack 90° 1.5 m</b> Right Angle Mono Jack 6,3mm - Mono Jack 6,3mm	1.5 meter	0,85	<b>1,02</b> EUR
		<b>HT Jack / Jack 90 GL3</b>			
	<b>HT Jack / Jack 90 GL3</b>	<b>Instruments Cable Jack 90° / Jack 90° 3 m</b> Right Angle Mono Jack 6,3mm - Mono Jack 6,3mm	3 meter	1,28	<b>1,54</b> EUR
		<b>HAT 2xJack / ST. Jack L1,5 (HT210LU15 HED)</b>			
	<b>HAT 2xJack / ST. Jack L1,5 (HT210LU15 HED)</b>	<b>Audio Cable 6.3mm Stereo Jack / 2 x 6.3mm Mono Jacks 1.5 m</b> 6.3mm Stereo Jack / 2 x 6.3mm Mono Jacks	1.5 meter	0,85	<b>1,02</b> EUR
	<b>HT 2RCA/2RCA75</b>	<b>Stereo Chinch / Chinch Cable 0.75 m</b> Double RCA - Double RCA cable (glued plastic RCA connectors - red & white)	0.75 meter	0,85	<b>1,02</b> EUR
<b>NEW</b>		<b>CAB-RCAX2/RCAx2- 1.5M (B)</b>			
	<b>CAB-RCAX2/RCAx2- 1.5M (B)</b>	<b>Stereo Chinch / Chinch Cable 1.5 m</b> Double RCA - Double RCA cable (glued plastic RCA connectors - red & white)	1.5 meter	2,13	<b>2,56</b> EUR
	<b>CAB-RCAX2/RCAx2- 3M (B)</b>	<b>Stereo Chinch / Chinch Cable 3 m</b> Double RCA - Double RCA cable (glued plastic RCA connectors - red & white)	3 meter	2,98	<b>3,58</b> EUR
<b>NEW</b>		<b>CAB-MJST/RCAx2-3M (B)</b>			
	<b>CAB-MJST/RCAx2-3M (B)</b>	<b>Notebook / PDA Cable Mini Stereo Jack / Stereo Chinch 3 m</b> Mini stereo jack 3,5mm - Double RCA	3 meter	2,98	<b>3,58</b> EUR
<b>NEW</b>		<b>CAB-MJST/JMOx2-3M (B)</b>			
	<b>CAB-MJST/JMOx2-3M (B)</b>	<b>Notebook / PDA Cable Mini Stereo Jack / 2 x Jack 3 m</b> Mini stereo jack 3,5mm - Double Mono Jack 6,3mm	3 meter	2,98	<b>3,58</b> EUR
<b>NEW</b>		<b>CAB-RCAX2/JMOx2- 3M (B)</b>			
	<b>CAB-RCAX2/JMOx2- 3M (B)</b>	<b>Double Mono Jack / 2 x Chinch Cable 3 m</b> Double Mono Jack 6,3m - Double RCA cable	3 meter	2,98	<b>3,58</b> EUR
<b>NEW</b>		<b>CAB-SP4/SP4-10M (B)</b>			
	<b>CAB-SP4/SP4-10M (B)</b>	<b>Speaker Cable Speakon / Speakon 2 x 2,5 mm² 10 m</b> 2 x 2,5mm² conductor=(65%copper,35%Aluminium)	10 meter	12,76	<b>15,31</b> EUR
	<b>NEW</b>	<b>HPC210 HED</b>			
		<b>HPC210 HED</b>			
	<b>HPC210 HED</b>	<b>Microphone Cable 2 x 022 mm²</b> 2 x 0,22mm² conductor + shield	meter	0,64	<b>0,77</b> EUR
	<b>NEW</b>	<b>HPC610 HED</b>			
		<b>HPC610 HED</b>			
	<b>HPC610 HED</b>	<b>Speaker Cable 2 x 1,5 mm² (16 AWG)</b> 2 x 1,5mm² conductor=(65%copper,35%Aluminium)	meter	0,85	<b>1,02</b> EUR
	<b>NEW</b>	<b>HPC620 HED</b>			
		<b>HPC620 HED</b>			
	<b>HPC620 HED</b>	<b>Speaker Cable 2 x 2,5 mm² (14 AWG)</b> 2 x 2,5mm² conductor=(65%copper,35%Aluminium)	meter	1,28	<b>1,54</b> EUR