



SANYO

Net Price List PROFESSIONAL USER

ALL PRICES AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

proTechnica

Pro-Sound & Lighting Solutions

www.pro-technica.com

BUY ONLINE at www.MusicWorld.bg

EUR

Price List 03/2013
Effective March 01, 2013




Subject to change without prior notice.

All former price lists expire with the publishing of this version.

All prices are suggested net retail prices; ex works.

There are applicable our General Terms of Business, only.

Aricles marked * will be discontinued soon!

E C P B R	Model	Description	EUR Netto (ex. VAT)	EUR + 20% DDS (incl. VAT)
DLP Projectors				
	 PLC-XL51A lamp: LMP-121 x 1	Data-/Videoprojector, Aspect Ratio 4:3 (Native), Brightness 2700 ANSI Lumens, Contrast Ratio 1200:1, Display Type 0.8" Polysilicon TFT LCD x 3, Resolution (Native / Max) XGA (1024 x 768), UXGA (1600 x 1200), Projection Lens F = 1.85, f = 0.19", Weight 7.71 kg, Connectivity Inputs 2 x RGB D-Sub 15pin, 1 x Stereo Mini Jack, 1 x Component, 1 x Composite, 1 x S-Video, 2 x RCA Audio, Audio 1 x 2W Mono Speaker, Control 1 x RJ-45, 1 x SD Card, Projection Screen Size (Diagonal) (152.4cm ~ 203.2cm), Throw Ratio 1.1:1, Optical Zoom 1.16:1, Vertical Keystone Correction +/- 5 Degrees	1.271,00	1.525,00 EUR
Business & Education				
	 PLC-XK2200 lamp: LMP-142 x 1	Data-/Videoprojector, Panel 3 x 0.55" TFT p-Si (4:3) with micro lens, Panel type Organic LCD panel, Lamp 220 W UHP (LMP-142), Brightness 2200 ANSI lumens, Standard lens F = 2.00 - 2.15 / f = 18.38 - 22.06 mm, Throw distance (standard lens) 1.3 - 11.8 m, Image size min. (WxH): 81.26 x 60.96 cm, Contrast ratio 2000 : 1 , Resolution in pixels 1024 x 768 (XGA), Uniformity 85 %, Connections Input 1: D-Sub15 (RGB/component/S-Video), Input 2: D-Sub15 (RGB) or monitor out, Input 3: RCA (composite), Audio: 3.5 mm stereo jack, Audio output : 3.5 mm stereo jack, Control input jack 1: D-Sub9 (RS232), Control input jack 2: RJ45 (LAN) , Audio function 1 W mono, Keystone correction vertical +/- 30°, Up/Down ratio Up/Down ratio 6 : 1 (fixed U/D ratio), Zoom/Focus 1.2 x/manual, Weight (net) 2.6 kg	419,00	503,00 EUR
Professional (1 lamp system)				
	 PLC-XP57L (w/o lens) (LMP-101)	Data-/Video projector, 5500 ANSI Lumen , XGA 1024x768 (VGA-SXGA with DRIT), contrast 1000:1, 7.9 kg, digital zoom, keystone-correction horizontal +/- 40°, vertical +/- 10°, vertical lens shift, 35 dB 300 Watt NSH Lamp, DVI-input, component-input, 5 interchangeable lenses, network manager (optional) Lamp life: 1500 hours / 2500 hours in eco-mode	2.985,00	3.582,00 EUR
DEMO Unit - 1399 EUR				
Professional (2 lamp system)				
	 PDG-DET100L lamp: LMP-130 x 2	Data-/Videoprojector, Panel: 1 x 0.95 " DMD Chip (4:3), Lamp: 2 x 330 W UHP (LMP-130), Brightness : 7500 ANSI lumens, Standard lens: Delivery without lens, Contrast ratio: 7500 : 1 , Resolution in pixels: 1400 x 1050 (S-XGA+), Uniformity: 90 %, Inputs: D-Sub15 (RGB) HDMI (HDCP), DVI-D (digital/HDCP), Mini DIN 4 (S-Video), 5 x BNC (RGBHV/Y-Pb/Cb-Pr/Cr), freely configurable input with optional interface boards, POA-MD13NET2 (RJ45(LAN)/D-Sub9), Monitor output: D-Sub15, Control Input Jack 1: D-Sub9 (RS232), Control Input Jack 2: 3.5 mm Stereo Jack (cable remote control), Control Input Jack 3: USB type B, Control output: D-Sub9 (RS232), Keystone correction, Weight (Net): 19.8 kg	8.498,00	10.198,00 EUR
	 PDG-DHT8000L lamp: LMP-145 x 2, 330W, price w/o VAT: 349 EUR	Data-/Video projector, Panel: 1 x 0.95" DMD chip (16:9), Lamp: 2 x 330 W UHP (LMP-145), Brightness: 8000 ANSI lumens, Lamp life: 3000 h (eco mode) / 2000 h (normal mode), Fan noise: 35 dB (eco mode) / 38 dB (normal mode), Standard lens: Delivery without lens, Image size min. (WxH): 110 x 62 cm, Image size max. (WxH): 1328 x 713 cm, Image size min. - max. (diagonal): 127 - 1524 cm, Image size min. - max. (diagonal): 50 - 600 inch, Contrast ratio: 7500 : 1 , Resolution in pixels: 1920 x 1080 (HDTV 1,080i), Uniformity: 90 %, Connections: Inputs: D-Sub15 (RGB) HDMI (HDCP), DVI-D, Mini DIN 4 (S-Video), 5 x BNC (RGBHV/Video/Y-Pb/Cb-Pr/Cr), freely configurable with optional interface boards, freely configurable input with optional interface boards, Monitor output: D-Sub15, Control input jack 1: D-Sub9 (RS232), Control input jack 2: RJ45 (LAN), Control input jack 3: 3.5 mm stereo jack (cable remote control)	11.050,00	13.260,00 EUR
Professional (4 lamp system)				
	 PLC-XF45	Data-/Video projector, 10000 ANSI Lumen , XGA 1024x768 (VGA-UXGA), contrast 1100:1 , Weight 37 kg , digital zoom, keystone correction vertical +40/-20°, vertical & horizontal lens shift, DVI-input, 11 optional lenses, 7 optional interfaces incl. network manager, 4 x 250 Watt UHP lamp system, Lamp life: 1000 hours	14.365,00	17.238,00 EUR
DEMO Unit - Price 2 990 EUR				
Special Water-, Oil-, Smoke-, Dustproof Professional LCD Monitors				
	42LM4WPR-E	42" (105 cm) LCD Professional monitor, IP Rating: IP56 Weather proof , Aspect Ratio: 16:9 , Resolution in pixels: 1366 x 768 (W-XGA), Pixel pitch in mm: 0.227 x 0.861, Brightness: 500 cd/m2 , Contrast Ratio: 800:1 , Viewing Angle: 178° (horizontal and vertical), Response time: 8 ms (gray to gray), Grey scale value: 8 bit, Number of colours: 16.7, Colour Systems: PAL, NTSC3.58 (AV in), Computer compatibility: UXGA, WXGA, SXGA, Input Terminals: HDMI (HDCP), D-Sub15, 5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr), Component (Y, Pb, Pr), BNC (Video), Scart (RGB), Video RS232 (D-Sub 9 pin), 2 x RCA (R/L mono) for Audio, Output Terminals: 5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr), Component (Y, Pb, Pr), BNC (Video), RS232 (D-Sub 9 pin), Scart (RGB), Video, 2 x RCA (R/L mono) for Audio, Tuner: VHF/UHF/Hyper 3 band, Aerial input impedance: 75 ohm, Operating Temperature: -20 °C to +45 °C, Storage Temperature: -20 °C to +50 °C, Maximum resilience: 100 N/mm2, Voltage: 220-240 V (50 Hz), Power Consumption: 230 W / 4.2 W (Stand-by mode), Dimensions (W x H x D): 1,050 x 654 x 162 mm, Weight: 39.5 kg , Packed Dimensions (W x H x D): 1,166 x 784 x 249 mm, Packed Weight: 43.5 kg, Vesa Mounting Sizes: 200 x 200 mm, Colour of cabinet: Silver, Standard accessories: user manual, remote control, batteries, Special feature: Fully sealed aluminium case, IP56°, vandalism-proof anti-reflective glass.	3.999,00	4.799,00 EUR

E C P B R

Model

Description

EUR	EUR
Netto	+ 20% DDS
(ex. VAT)	(incl. VAT)

Lenses for PLC-XT20, XT25

PLC-LNS-W10		Sold Out	EUR
PLC-LNS-W11		Sold Out	EUR
PLC-LNS-T10		Sold Out	EUR
PLC-LNS-S10	Lens for PLC XT Range, Standard zoom, Zoom: motorized (1,3x), Focus: motorized, f:33-43mm	276,00	331,00 EUR
PLC-LNS-S11	Wide-angle zoom, Zoom: motorized (1,3x), Focus: mototized, Aperture (F): 1.7 - 2.1, Focal Length (f): 33 - 43 mm, Diameter: 90 mm, Weight: 0.8 kg, Throw Distance Ratio: 1.62 - 2.11 : 1	250,00	300,00 EUR
PLC-LNS-T11	Tele lens (motorized zoom + focus), f = 69 - 109mm, F 2.1 - 2.5 aspect ratio: 3.4 - 5.4 :1, lens shift: 10:0 - 1:1, one-touch-lens mount-system	1.658,00	1.990,00 EUR

Lenses for PLC-XP57/L, PLC-XP100, PLC-XP200, PLV-80

PLC-LNS-S31		Sold Out	EUR
PLC-LNS-T31A		1.381,00	1.657,00 EUR
PLC-LNS-T32		Sold Out	EUR
PLC-LNS-T33		Sold Out	EUR



PLC-LNS-W31A	Wide angle lens, motorized zoom + focus, f = 34.3 - 48mm, F= 2.5 - 3.1	1.381,00	1.657,00 EUR
PLC-LNS-W32E		Sold Out	EUR

Lenses for PLC-XF42, XF46E, XF60A, UF15, PLV-WF10, HD2000I

PLC-LNS-S02Z		Sold Out	EUR
PLC-LNS-S03		Sold Out	EUR
PLC-LNS-S04		Sold Out	EUR
PLC-LNS-M01E		Sold Out	EUR
PLC-LNS-M02		Sold Out	EUR
PLC-LNS-T01Z		Sold Out	EUR
PLC-LNS-T02E		Sold Out	EUR
PLC-LNS-T03		Sold Out	EUR
PLC-LNS-W02Z		Sold Out	EUR
PLC-LNS-W03E		Sold Out	EUR
PLC-LNS-W04		Sold Out	EUR
PLC-LNS-W06		Sold Out	EUR

Lenses for XM, WM, ZM

PLC-LNS-S20		Sold Out	EUR
PLC-LNS-T20		Sold Out	EUR
PLC-LNS-T21		Sold Out	EUR
PLC-LNS-W20		Sold Out	EUR
PLC-LNS-W21		Sold Out	EUR

Lenses for DHT, DET

PLC-LNS-S51	Standard zoom, Zoom: motorized, Focus: motorized, f=2.0 - 2.6, F=38.5 - 60.0	2.011,00	2.413,00 EUR
-------------	--	----------	---------------------



PLC-LNS-W52	Extreme Wide Angle, Fixed 17mm	2.685,00	3.222,00 EUR
-------------	--------------------------------	----------	---------------------

PLC-LNS-W53		2.210,00	2.652,00 EUR
-------------	--	----------	---------------------



PLC-LNS-T50	Tele Zoom Motorized, f= 59.3 - 107mm	3.177,00	3.812,00 EUR
-------------	--------------------------------------	----------	---------------------



PLC-LNS-T51	Extrem Tele Zoom, Motorized, f=101-169mm	3.238,00	3.886,00 EUR
-------------	--	----------	---------------------