

Price List 04/2015



Net Price List PROFESSIONAL USER

ALL PRICES AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

proTechnica

Pro-Audio & Lighting Solutions

www.pro-technica.com

BUY ONLINE at www.MusicWorld.bg

Effective April 6-th, 2015

Subject to change without prior notice.
All former price lists expire with the publishing of this version.
If prices are suggested net retail prices; ex works.
There are applicable our General Terms of Business, only.

EUR

Articles marked with PHO (phase out) will be discontinued soon!

Model

Description

EUR
Netto + 20% DDS
(ex. VAT) (incl. VAT)

Mixers

LIVE Series



LIVE 802

PROFESSIONAL 8-CHANNEL/2-BUS MIXER

- 5 XLR inputs with DNA™ microphone preamps • Dynamic compression (channels 1-2)
- 3-band EQ plus 2 aux sends per channel • 60mm faders with mute switch and LED
- USB audio connectivity with level control • 100 Alesis DSP effects • Balanced XLR, balanced/unbalanced 1/4" outputs • 9-band graphic EQ for main or monitor outputs • Headphone out with independent level control

193,00

232,00 EUR



LIVE 1202

Professional 12-Channel/2-Bus Mixer

- 7 XLR inputs with high-DNA™ mic preamps • Dynamic compression (Channels 1-4)
- 3-band EQ plus 2 aux sends per channel • 60mm faders with mute switch and LED meters
- USB audio connectivity with level control • 100 Alesis DSP effects • Balanced XLR, balanced/unbalanced 1/4" outputs • 9-band graphic EQ for main or monitor outputs • Headphone out with independent level control

226,00

271,00 EUR



LIVE 1604

PROFESSIONAL 16-CHANNEL/4-BUS MIXER

- 10 XLR inputs with DNA(TM) microphone preamps • Dynamic compression (channels 1-6)
- 3-band EQ with sweepable mids • 4 aux sends; pre/post switching on sends 1+2 • 60mm faders with mute and PFL/AFL solo functions • 100 Alesis DSP effects
- USB audio connectivity with level control • Balanced XLR, balanced/unbalanced 1/4" outputs • Headphone out with independent level control • Switchable Phantom Power

335,00

402,00 EUR



LIVE 2404

Professional 24-Channel/4-Bus Mixer

- 18 XLR inputs with DNA(TM) microphone preamps • Dynamic compression (channels 1-8)
- 3-band EQ with sweepable mids • 4 aux sends; pre/post switching on sends 1+2 • 60mm faders with mute and PFL/AFL solo functions • 100 Alesis DSP effects
- USB audio connectivity with level control • Balanced XLR, balanced/unbalanced 1/4" outputs • Headphone out with independent level control • Switchable Phantom Power

494,00

593,00 EUR

ZMX series



ZMX52

5-Channel Compact Mixer • Six total inputs including an XLR jack with phantom power and EQ on Channel 1 • 1/4" Main, Tape, Headphone and Aux outputs for flexible routing and monitoring • Compact design perfect for musicians looking for easy portage and quick set-up • Mic input channel with gold plated XLR and balanced line input • Two stereo input channels with balanced TRS jack • Extremely high headroom offering extra dynamic range • Ultra-low-noise discrete mic preamps with +18V Phantom power • Balanced inputs for highest signal integrity and low-noise operation • Warm, natural two-band EQ on mono channel • Peak LEDs on each channel • 2-Track inputs with level control assignable to main mix, headphone outputs • Highly accurate four-segment bar graph meters;

44,00

53,00 EUR



ZMX862

6-Channel Compact Mixer • Eight total inputs including XLR jacks with phantom power on channels one and two • Two mic input channels with gold plated XLR and balanced line inputs • Two stereo input channels with balanced TRS jacks • Extremely high headroom offering extra dynamic range • Three-shelf EQ on each mono and stereo channel • Two aux sends per-channel for external effects and monitoring • Two bus design with Main and Control Room 1/4" stereo outputs

71,00

85,00 EUR



ZMX122FX

8-Channel Compact Mixer with Effects • 12 total inputs including XLR jacks with phantom power on channels one through four • Four mic input channels with gold plated XLR and balanced line inputs • Two stereo input channels with balanced TRS jacks • Extremely high headroom offering extra dynamic range • Three-band EQ on each channel • On-board digital effects processor and three-shelf EQ on each mono and stereo channel • Footswitch input for effects bypass (footswitch not included) • Two aux sends pre-channel for external effects and monitoring • Two bus design with Main and Control Room 1/4" stereo outputs

111,00

133,00 EUR



ZMX124FX USB **

12-Channel Mixer with Effects and USB Interface • 20 total inputs • 3-band EQ with swept mid on microphone channels • 4-band fixed EQ on stereo line channels • Stereo 9-band graphic EQ • 4 AUX sends per channel: 2 PRE/POST faders switchable • 4-bus sub mixer • 60mm high precision faders • 256 24-bit Alesis DSP effects (16 presets × 16 variations) • USB audio interface for computer software recording and monitoring

213,00

256,00 EUR



ZMX164FX USB **

16-Channel Mixer with Effects and USB Interface • 28 total inputs • 3-band EQ with swept mid on microphone channels • 4-band fixed EQ on stereo line channels • Stereo 9-band graphic EQ • 4 AUX sends per channel: 2 PRE/POST faders switchable • 4-bus sub mixer • 60mm high precision faders • 256 24-bit Alesis DSP effects (16 presets × 16 variations) • USB audio interface for computer software recording and monitoring

256,00














307,00 EUR

| Model | Description | EUR Netto (ex. VAT) | EUR + 20% DDS (incl. VAT) |
|---|---|---------------------------|---------------------------------|
| Empire Series | | | |
|  | 8-Channel Powered Mixer with Effects • 14 total inputs including 4 XLR jacks with phantom power, 8 Line jacks and stereo RCA • On-board digital effects processor and 3-shelf EQ on each mono and stereo channel • 1400 Watt peak, Continuous 2 x 350 Watts at 4 Ω (2 x 180 W at 8 Ω) with thermal, short and voltage protections • 48V phantom power | 373,00 | 448,00 EUR |
|  | 12-Channel Powered Mixer with Effects • 22 total inputs including 8 XLR jacks with phantom power, 12 Line jacks and stereo RCA • On-board digital effects processor and 3-shelf EQ on each mono and stereo channel • 1400 Watt peak, Continuous 2 x 500 Watts at 4 Ω (1000 W at 8 Ω bridged) with thermal, short and voltage protections • 48V phantom power | 409,00 | 491,00 EUR |
|  | 16-Channel Powered Mixer with Effects • 30 total inputs including 12 XLR jacks with phantom power, 16 Line jacks and stereo RCA • On-board digital effects processor and 3-shelf EQ on each mono and stereo channel • Continuous 2 x 750 Watts at 4 Ω (1500 W at 8 Ω bridged) with thermal, short and voltage protections • 48V phantom power | 435,00 | 522,00 EUR |
|  | 20-Channel Powered Mixer with Effects • 38 total inputs including 16 XLR jacks with phantom power, 20 Line jacks and stereo RCA • On-board digital effects processor and 3-shelf EQ on each mono and stereo channel • Continuous 2 x 750 Watts at 4 Ω (1500 W at 8 Ω bridged) + 1000 Watts at 8 Ω bridged) with thermal, short and voltage protections • 48V phantom power | 684,00 | 821,00 EUR |
|  | 500 Watt Powered Cabinet Mixer with Effects • 18 total inputs including 8 XLR jacks with phantom power, 8 line jacks and stereo RCA • On-board digital effects processor and 3-shelf EQ on each mono and stereo channel • Continuous 2 x 250W power at 4-ohms; 500W at 8-ohms Bridged • Class D Power for clean power and light weight • Built-in, recessed handles for easy transport | 281,00 | 337,00 EUR |
|  | 1000 Watt Powered Cabinet Mixer with Effects • 18 total inputs including 8 XLR jacks with phantom power, 8 line jacks and stereo RCA • On-board digital effects processor and 3-shelf EQ on each mono and stereo channel • Continuous 2 x 500W power at 4-ohms; 1000W at 8-ohms Bridged • Class D Power for clean power and light weight • Built-in, recessed handles for easy transport | 303,00 | 364,00 EUR |
|  | 1500 Watt Powered Cabinet Mixer with Effects • 18 total inputs including 8 XLR jacks with phantom power, 8 line jacks and stereo RCA • On-board digital effects processor and 3-shelf EQ on each mono and stereo channel • Continuous 2 x 740W power at 4-ohms; 1550W at 8-ohms Bridged • Class D Power for clean power and light weight • Built-in, recessed handles for easy transport | 399,00 | 454,00 EUR |
| Speakers & PA | | | |
| TOURMAX ARRAY | | | |
|  | Professional 2-way Line Array Loudspeaker • 1600 Watts peak power rating • Dual 8" LF drivers • Dual 1" HF drivers • Quick and easy to set up for a wide variety of configurations • Optimized for short or medium-throw, indoors or out • Maximum SPL @ 1m: 125dB Peak (Passive Mode) • Ideal for fixed installations or rentals | 1.065,00 | 1.278,00 EUR |
|  | 18" Vented Line Array Subwoofer • 3000 Watts peak power rating • 18" Vented Subwoofer • Optimized for short or medium-throw • Suitable for indoor or outdoor installation • Configurable in a stereo system, mono center, or delay tower • Compact design perfect for fixed installation or renting | 711,00 | 853,00 EUR |
| TOURMAX SX Series | | | |
|  | 2-Way 12" Passive Loudspeaker • 800 Watts peak power rating • 400 Watts program / 200 Watts continuous • 12" low-frequency transducer • 1" neodymium high-frequency driver • Full-length metal grille • Two parallel Speakon NL4 jacks for input and through connections • Lightweight, trapezoidal cabinet with handles • Rugged, black textured finish | 125,00 | 150,00 EUR |
|  | 2-Way 15" Passive Loudspeaker • 1200 Watts peak power rating • 600 Watts program / 300 Watts continuous • 15" low-frequency transducer • 1" neodymium high-frequency driver • Full-length metal grille • Two parallel Speakon NL4 jacks for input and through connections • Lightweight, trapezoidal cabinet with handles • Rugged, black textured finish | 169,00 | 203,00 EUR |
|  | Dual 15" 2-Way Passive Speaker System • 2000 Watts peak power rating • 1000 Watts program / 500 Watts continuous • Two 15" low-frequency transducer • 1" neodymium high-frequency driver • Full-length metal grille • Two parallel Speakon NL4 jacks for input and through connections • Lightweight, trapezoidal cabinet with handles • Rugged, black textured finish | 260,00 | 312,00 EUR |
|  | Active Powered 800 Watt 2-Way Stage Monitor • 800 Watts Class D power • 12" coax woofer, 1" neodymium driver • XLR/Line input with volume control, XLR output to link speakers • 16 modeling presets to tweak the sonic characteristic of your sound • Rugged multi-layer birch plywood cabinet with recessed handles • Scratch and dent-resistant finish | 240,00 | 288,00 EUR |
|  | 15" Passive Subwoofer • 1600 Watts peak power rating • 800 Watts program / 400 Watts continuous • 15" low-frequency transducer, 3" voice coil • Two parallel Speakon NL4 jacks for input and through connections, passive crossover on through • Durable and compact cabinet with metal handle | 233,00 | 280,00 EUR |
|  | 18" Passive Subwoofer • 1600 Watts peak power rating • 800 Watts program / 400 Watts continuous • 18" low-frequency transducer, 3" voice coil • Two parallel Speakon NL4 jacks for input and through connections, passive crossover on through • Durable and compact cabinet with metal handle | 336,00 | 403,00 EUR |

Model

Description

TX Active Series

| | | | | |
|---|---------------------|--|--------|-------------------|
|  | NEW TX-8 | 280-WATT 8-INCH 2-WAY ACTIVE LOUDSPEAKER • 280 Watts peak / 140 Watts continuous power • Efficient Class-D power amp, bi-amplified • 8" LF woofer with 1.5" voice coil • 1" titanium diaphragm HF compression driver with 1" voice coil • Balanced XLR Mic/Line Input & Link Output • Precision electronic crossover • Integrated analog limiter and overload protection circuitry • Lightweight, portable design • Integrated 36mm speaker pole socket • Main or wedge monitor operation • Designed in the USA | 120,00 | 144,00 EUR |
|  | NEW TX-10 | 280-WATT 10-INCH 2-WAY ACTIVE LOUDSPEAKER • 280 Watts peak / 140 Watts continuous power • Efficient Class-D power amp, bi-amplified • 10" LF woofer with 1.5" voice coil • 1" titanium diaphragm HF compression driver with 1" voice coil • Balanced XLR Mic/Line Input & Link Output • Precision electronic crossover • Integrated analog limiter and overload protection circuitry • Lightweight, portable design • Integrated 36mm speaker pole socket • Main or wedge monitor operation • Designed in the USA | 155,00 | 186,00 EUR |
|  | NEW TX-12 | 600-WATT 12-INCH 2-WAY ACTIVE LOUDSPEAKER • 600 Watts peak / 300 Watts continuous power • Efficient Class-D power amp, bi-amplified • 12" LF woofer with 2" voice coil • 1" neodymium HF compression driver with 1" voice coil • Balanced XLR Combo Mic/Line Input Link Output • Precision electronic crossover • Onboard Contour control • Integrated analog limiter and overload protection circuitry • Lightweight, portable design • Integrated 36mm speaker pole socket • Main or wedge monitor operation • Dimensions (HxWxD): 607 x 380 x 337mm • Net weight: 13.75kg | 200,00 | 240,00 EUR |
|  | NEW TX-15 | 600-WATT 15-INCH 2-WAY ACTIVE LOUDSPEAKER • 600 Watts peak / 300 Watts continuous power • Efficient Class-D power amp, bi-amplified • 15" LF woofer with 2" voice coil • 1" neodymium HF compression driver with 1" voice coil • Balanced XLR Combo Mic/Line Input & Link Output • Onboard Contour control • Precision electronic crossover • Integrated analog limiter and overload protection circuitry • Lightweight, portable design • Integrated 36mm speaker pole socket • Main or wedge monitor operation • Dimensions (HxWxD): 625 x 386 x 366mm • Net weight: 14.86 kg • Designed in the USA | 215,00 | 258,00 EUR |
| TRUESONIC TS Series | | | | |
|  | TS110A | Active 600 Watt 2-Way 10" Loudspeaker • 600 Watts Class D power • 10" low-frequency transducer, 1" neodymium driver • Two Mic/Line combo inputs with independent volume controls • XLR output to link speakers • Lightweight, trapezoidal cabinet with handle • Stand and pole-mountable or flyable • Clip Limiter with red LED • Ground Lift switch • Contour switch for increased EQ control • Accurate audience coverage, not just on-axis • Use as traditional upright loudspeaker or as floor wedge monitor • Designed and tuned in the USA | 248,00 | 298,00 EUR |
|  | TS112A | Active 800 Watt 2-Way 12" Loudspeaker • 800 Watts Class D power • 12" low-frequency transducer, 1" neodymium driver • Two Mic/Line combo inputs with independent volume controls • XLR output to link speakers • Lightweight, trapezoidal cabinet with handle • Stand and pole-mountable or flyable • Clip Limiter with red LED • Ground Lift switch • Contour switch for increased EQ control • Accurate audience coverage, not just on-axis • Use as traditional upright loudspeaker or as floor wedge monitor • Designed and tuned in the USA | 266,00 | 319,00 EUR |
|  | TS112 | Passive 800 Watt 2-Way 12" Loudspeaker • 800 Watt peak power rating • 400 Watts program / 200 Watts continuous • Dual electronic driver protection circuits • Compact, lightweight design, trapezoidal cabinet design for easy transport and installation • Used as traditional loudspeaker or as floor wedge monitor • Two parallel Speakon NL4 jacks for input and through connection • Stand and pole-mountable or flyable • Designed and tuned in the USA | 171,00 | 205,00 EUR |
| | SPKRCVR 12 | Padded Speaker Cover • for TS 112 & TS 112A | 25,00 | 30,00 EUR |
|  | TS115A | Active 800 Watt 2-Way 15" Loudspeaker • 800 Watts Class D power • 15" low-frequency transducer, 1" neodymium driver • Two Mic/Line combo inputs with independent volume controls • XLR output to link speakers • Lightweight, trapezoidal cabinet with handle • Stand and pole-mountable or flyable • Clip Limiter with red LED • Ground Lift switch • Contour switch for increased EQ control • Accurate audience coverage, not just on-axis • Use as traditional upright loudspeaker or as floor wedge monitor • Designed and tuned in the USA | 280,00 | 336,00 EUR |
|  | TS115 VIBE | Active 800 Watt 2-Way 15" Loudspeaker with MEDIA PLAYER • 800 Watts Class D power • 15" low-frequency transducer, 1" neodymium driver • Onboard solid-state media player with volume control • Load your favorite music via USB drive or microSD card • Compatible with MP3, WMA, and AAC files • Features include Folder Search and ID3 Tagging Built-in two-channel mixer with independent volume controls • Two Mic/Line combo inputs with independent volume controls • XLR output to link speakers • Lightweight, trapezoidal cabinet with handle • Stand and pole-mountable or flyable • Clip Limiter with red LED • Ground Lift switch • Contour switch for increased EQ control • Accurate audience coverage, not just on-axis • Use as traditional upright loudspeaker or as floor wedge monitor • Designed and tuned in the USA | 320,00 | 384,00 EUR |
|  | TS115 | Passive 1000 Watt 2-Way 12" Loudspeaker • 1000 Watt peak power rating • 500 Watts program / 250 Watts continuous 500 Watt program / 250 Watt continuous • 15" LF transducer with 2.5" voice coil, 1" neodymium HF driver • Dual electronic driver protection circuits • Lightweight, trapezoidal cabinet with handles • Two parallel Speakon NL4 jacks for input and thru connection • Use as a traditional upright loudspeaker or as floor wedge monitor • Stand and pole-mountable or flyable • Designed and tuned in the USA | 200,00 | 240,00 EUR |
| | SPKRCVR 15 | Padded Speaker Cover • for TS 115 & TS 115A | 25,00 | 30,00 EUR |
|  | TS SUB12 | Active 600 Watt 12" Subwoofer • 600 Watts Class D power • Powerful 12" woofer with 2.5" voice coil and double ventilation • Stereo Inputs: Mic/Line left channel, XLR right channel • Stereo XLR outputs: Left link, Right mono, internal crossover on through • Compact 18 mm birch cabinet with metal grille and handles • Adjustable level and polarity controls • Integrated hi-pass / low-pass filter • Clip Limiter with red LED • Ground Lift switch | 258,00 | 310,00 EUR |
|  | TS SUB15 | Active 1200 Watt 15" Subwoofer • 1200 Watts Class D power • Powerful 15" low-frequency, long-excursion driver • Stereo inputs: Mic/Line left channel, XLR right channel • Stereo XLR outputs: Left link, Right mono, internal 120Hz crossover on through • 18 mm birch plywood vented cabinet with metal grille and recessed handles Adjustable level and polarity controls • 35 mm pole socket | 361,00 | 433,00 EUR |
|  | TS SUB18 | Active 1200 Watt 18" Subwoofer • 1200 Watts Class D power • Powerful 18" low-frequency, long-excursion driver • Stereo inputs: Mic/Line left channel, XLR right channel • Stereo XLR outputs: Left link, Right mono, internal 120Hz crossover on through • 18 mm birch plywood vented cabinet with metal grille and recessed handles Adjustable level and polarity controls • 35 mm pole socket | 439,00 | 527,00 EUR |

| | |
|-------|-------------|
| Model | Description |
|-------|-------------|

TRUESONIC Wireless Series for iPhone & iPad



TS112W

Active 800 Watt 2-Way 12" Loudspeaker with Wireless Connectivity • Built-in Bluetooth® A2DP wireless technology* • Stream audio wirelessly from iPad, iPhone, iPod touch, Android devices and more • Stream stereo signal, left and right, to separate speakers—no cables required • Use as traditional PA loudspeaker or as floor wedge monitor • 800 Watts Class D power • 12" low-frequency transducer, 1" neodymium driver • Two mic/line combo inputs with independent volume controls • XLR output to link speakers • Lightweight, trapezoidal cabinet with handles • Stand and pole-mountable or flyable • Contour switch for increased EQ control • Clip Limiter with red LED • Ground Lift switch • Accurate audience coverage, not just on-axis • Designed and tuned in the USA

314,00

377,00 EUR

TS115W

Active 800 Watt 2-Way 15" Loudspeaker with Wireless Connectivity • Built-in Bluetooth® A2DP wireless technology* • Stream audio wirelessly from iPad, iPhone, iPod touch, Android devices and more • Stream stereo signal, left and right, to separate speakers—no cables required • Use as traditional PA loudspeaker or as floor wedge monitor • 800 Watts Class D power • 15" low-frequency transducer, 1" neodymium driver • Two mic/line combo inputs with independent volume controls • XLR output to link speakers • Lightweight, trapezoidal cabinet with handles • Stand and pole-mountable or flyable • Contour switch for increased EQ control • Clip Limiter with red LED • Ground Lift switch • Accurate audience coverage, not just on-axis • Designed and tuned in the USA

337,00

404,00 EUR

TRUESONIC IPA Series system for iPad



IPA Music System**

400 Watt Powered 2-Way 10" Speaker for iPad • Two-way speaker system with 400 Watts of peak power • Fully integrated Universal Dock for iPad • Includes Alto Professional ADM10 dynamic mic, holder and 10-foot (3m) cable • Integrated mixer and high-efficiency power amp • 10-inch (254 mm) low frequency transducer for deep bass • Compact lightweight design for easy transport • 35 mm socket for mounting on a speaker stand • Designed and tuned in the USA • 30-pin dock also charges iPad • Contour switch instantly provides the perfect EQ for music playback and karaoke • RCA input for playback of iPod, CD players and other music devices • XLR-1/4" combo inputs with volume control • XLR output to add more speakers • 200 Watts of continuous power

259,00

311,00 EUR

BLACK Series



BLACK 10

10" 2-WAY 2400 WATT LOUDSPEAKER WITH WIRELESS CONNECTIVITY

• 2400 Watts peak Class D power (1200 Watts continuous) • Unrivaled acoustic accuracy via advanced engineering and design • Works with free Live Drive app for wireless sound-shaping control • Wirelessly level-match, EQ, delay-compensation, and more • 10" LF transducer, 1.75" HF driver with 1" acoustic aperture, 90° x 60° coverage field • DSP-controlled active crossover and dynamic thermal protection • HF waveguide, computer-designed for optimized audience coverage • Purpose-matched components for maximum efficiency • Built-in mixer, (2) Mic/Line inputs, volume control, XLR output • EQ contour switch, Ground Lift switch, plus switch to turn off logo LED • Lightweight, portable design with custom-molded handle • Post as traditional PA loudspeaker or as floor wedge monitor • Steel-reinforced rubber feet on bottom and side • Rugged cabinet, scratch-resistant finish, powder-coated steel grille • Stand- and pole-mountable via standard 35mm socket • Flyable via (12) M10 rigging points • Designed and tuned in the U.S.A.

602,00

722,00 EUR



BLACK 12

12" 2-WAY 2400 WATT LOUDSPEAKER WITH WIRELESS CONNECTIVITY

• 2400 Watts peak Class D power (1200 Watts continuous) • Unrivaled acoustic accuracy via advanced engineering and design • Works with free Live Drive app for wireless sound-shaping control • Wirelessly level-match, EQ, delay-compensation, and more • 12" LF transducer, 1.75" HF driver with 1" acoustic aperture, 90° x 60° coverage field • DSP-controlled active crossover and dynamic thermal protection • HF waveguide, computer-designed for optimized audience coverage • Purpose-matched components for maximum efficiency • Built-in mixer, (2) Mic/Line inputs, volume control, XLR output • EQ contour switch, Ground Lift, and switch to turn off logo LED • Lightweight, portable design with custom-molded handles • Post as traditional PA loudspeaker or as floor wedge monitor • Steel-reinforced rubber feet on bottom and side • Rugged cabinet, scratch-resistant finish, powder-coated steel grille • Stand- and pole-mountable via standard 35mm socket • Flyable via (12) M10 rigging points • Designed and tuned in the U.S.A.

704,00

845,00 EUR



BLACK 15

15" 2-WAY 2400 WATT LOUDSPEAKER WITH WIRELESS CONNECTIVITY

• 2400 Watts peak Class D power (1200 Watts continuous) • Unrivaled acoustic accuracy via advanced engineering and design • Works with free Live Drive app for wireless sound-shaping control • Wirelessly level-match, EQ, delay-compensation, and more • 15" LF transducer, 1.75" HF driver with 1" acoustic aperture, 90° x 60° coverage field • DSP-controlled active crossover and dynamic thermal protection • HF waveguide, computer-designed for optimized audience coverage • Purpose-matched components for maximum efficiency • Built-in mixer, (2) Mic/Line inputs, volume control, XLR output • EQ contour switch, Ground Lift, and switch to turn off logo LED • Lightweight, portable design with custom-molded handles • Post as traditional PA loudspeaker or as floor wedge monitor • Steel-reinforced rubber feet on bottom and side • Rugged cabinet, scratch-resistant finish, powder-coated steel grille • Stand- and pole-mountable via standard 35mm socket • Flyable via (12) M10 rigging points • Designed and tuned in the U.S.A.

817,00

980,00 EUR



BLACK 15S

2400 WATT 15" ACTIVE SUBWOOFER

• 2400 Watts peak Class D power (1200 Watts continuous) • Unrivaled acoustic accuracy via advanced engineering and design • Works with free Live Drive app for wireless sound-shaping control • Wirelessly level-match, EQ, delay-compensation, and more • Stereo XLR outputs: left link, right mono, internal crossover on through • Rugged cabinet, scratch-resistant finish, powder-coated steel grille • Portable design with comfortable, custom-molded handles • Powerful 15" low-frequency, long-excursion driver • Stereo inputs: Mic/Line left channel, XLR right channel • Purpose-matched components for maximum efficiency • Adjustable level and polarity controls • Switch to turn off logo LED • Steel-reinforced rubber feet • Standard 35mm pole socket • Flyable via (12) M10 rigging points • Designed and tuned in the U.S.A.

812,00

974,00 EUR



BLACK 18S

2400 WATT 18" ACTIVE SUBWOOFER

• 2400 Watts peak Class D power (1200 Watts continuous) • Unrivaled acoustic accuracy via advanced engineering and design • Works with free Live Drive app for wireless sound-shaping control • Wirelessly level-match, EQ, delay-compensation, and more • Stereo XLR outputs: left link, right mono, internal crossover on through • Rugged cabinet, scratch-resistant finish, powder-coated steel grille • Portable design with comfortable, custom-molded handles • Powerful 18" low-frequency, long-excursion driver • Stereo inputs: Mic/Line left channel, XLR right channel • Purpose-matched components for maximum efficiency • Adjustable level and polarity controls • Switch to turn off logo LED • Steel-reinforced rubber feet • Standard 35mm pole socket • Flyable via (12) M10 rigging points • Designed and tuned in the U.S.A.

920,00

1.104,00 EUR

MIXPACK Series



MIXPACK Express

Ultra-Portable Powered PA System • 350 Watts of continuous power • Lightweight, one-piece design for convenient transport • Two 10" speakers with cables included • Built-in mixer with seven-band graphic EQ and XLR, line and RCA inputs • Integrated Alesis DSP with 24-bit effects including reverb, delay and chorus

351,00

421,00 EUR

Model Description

TROUPER PA System



NEW
TROUPER

Compact High-Performance PA System

- Integrated 3-channel professional audio mixer with volume and 2-band EQ on each channel
- (2) XLR+1/4-inch combo inputs + stereo RCA and 1/8-inch inputs. Connect microphones, instruments, DJ mixers, controllers and more
- Bluetooth-equipped-wirelessly stream backing tracks or background music from any Bluetooth-compatible device
- Bluetooth Link-Stream a stereo signal to separate speakers—no cables required
- Bi-amplified design with (3) 6.5-inch low/mid woofers and a 1-inch high-frequency tweeter
- XLR link output for use with additional loudspeakers and subwoofers
- Easily transportable: Lightweight (just 23 lbs.) with built-in rear handle
- Rubberized feet and 36mm pole socket for stand mounting

215,00 **258,00** EUR

MI Amplification



KICK12

- 400 Watt Instrument Amplifier/PA** • 4-channel mixer with stereo line inputs on each channel and an XLR input on Channel 1 • 400 Watts peak power, 200 Watts continuous • 12" low-frequency transducer, 1" compression driver • Custom-tuned electronic crossover provides superb frequency response • True bi-amped design provides dedicated power to high and low drivers • Built-in Alesis digital effects processor with reverb, delay, chorus, and more • 256 effect presets: 16 effects with 16 variations each • Integrated folding steel kickstand provides the ideal monitoring angle • Level, effects, and high & low EQ controls on all four channels • Stereo RCA input for connecting MP3 players and other audio devices • Footswitch input allows instant activation or bypass of effects • 1/4" headphone output with dedicated volume control • Angled speaker baffle for optimized throw • Dual XLR and 1/4" Mix outputs • Ground Lift switch

275,00 **330,00** EUR



KICK15

- 400 Watt Instrument Amplifier/PA** • 4-channel mixer with stereo line inputs on each channel and an XLR input on Channel 1 • 400 Watts peak power, 200 Watts continuous • 15" low-frequency transducer, 1" compression driver • Custom-tuned electronic crossover provides superb frequency response • True bi-amped design provides dedicated power to high and low drivers • Built-in Alesis digital effects processor with reverb, delay, chorus, and more • 256 effect presets: 16 effects with 16 variations each • Integrated folding steel kickstand provides the ideal monitoring angle • Level, effects, and high & low EQ controls on all four channels • Stereo RCA input for connecting MP3 players and other audio devices • Footswitch input allows instant activation or bypass of effects • 1/4" headphone output with dedicated volume control • Angled speaker baffle for optimized throw • Dual XLR and 1/4" Mix outputs • Ground Lift switch

322,00 **386,00** EUR

Electronic components

Processors

HPA6



- 6-Channel Stereo Headphone Amplifier** • Six independent high-power headphone amplifiers in a compact, 1RU size • Supplies six fully independent mixes for up to 18 pairs of headphones • Stereo Aux Input on each channel level adjustments for click/loop monitoring • Additional Direct Input on front panel: mix in additional sources instantly • Four-segment LED on each channel for easy visual monitoring • Mono and Left/Right Mutes per channel for two mono mixes per channel • High-quality components and exceptionally rugged construction • Servo-balanced, gold-plated XLR and 1/4" TRS connectors

124,00 **149,00** EUR

ACOM2



- 2-Channel Compressor / Limiter / Gate** • Two independent, full-featured compressor/limiters in one compact rack • Use as two individual mono processors, or stereo-link to provide true stereo compression • Auto-attack/-release switch automatically adjusts compression to source signal • Full manual mode for tailored adjustment to any venue • Minimized signal path with high-quality VCA: low noise, minimal distortion and optimal temperature stability • Intelligent Knee for musical performance with soft and hard-knee envelopes • Couple switch for a one-touch selection between two mono channels or stereo-linked operation • Sidechain send and return for use in an external effects loop • Switchable low-cut filter minimizes audio-program pumping triggered by kick drum • Gain-reduction LEDs and switchable input/output-level LED meters for visual monitoring of critical values • Bypass switches on both channels

124,00 **149,00** EUR

AX2304



- Professional High-Precision Stereo 2-Way / 3-Way / Mono 4-Way Crossover** • Absolutely flat summed amplitude response with zero phase difference • 24 dB-per-octave Linkwitz-Riley filters • Individual output level controls for all bands • Limiters on each output for optimal loudspeaker protection • Independent output mutes for easy band adjustment • Individual phase reverse switches for instant phase correction • Switchable 25 Hz subsonic filter on each input for low-frequency driver protection • Low Sum function provides low-level mono output for subwoofer operation • Adjustable time delay for phase alignment between drivers • CD horn equalization for constant directivity horn compensation • Servo-balanced, gold-plated XLR connectors for all inputs and outputs • Ultra-high-precision potentiometers for ultimate accuracy and repeatability • High-quality components and exceptionally rugged construction for long life and reliability • Shielded toroidal mains transformer for minimal noise interference

103,00 **124,00** EUR

AEQ215



- Stereo 15-Band Graphic EQ** • Balanced XLR, 1/4" TRS and RCA input and output connectors • Standard 20 mm center-detented sliders allow easy frequency adjustment • Constant Q filtering provides accurate and predictable EQ response • Selectable boost/cut range of 6 dB or 12 dB for more precise gain control • High-pass filter: 40 Hz (12 dB/octave) • Low-pass filter: 16 kHz (12 dB/octave) • 2/3-octave spacing • Variable input level control • EQ bypass switch on both channels • Clip level indicators • Ground lift switch to disconnect signal ground from chassis ground

124,00 **149,00** EUR

AEQ231



- Stereo 31-Band Graphic EQ** • Balanced XLR, 1/4" TRS and RCA input and output connectors • 1/3-octave spacing provides precise, sound-shaping control • Standard 20 mm center-detented sliders allow easy frequency adjustment • Selectable boost/cut range of 6 dB or 12 dB for more precise gain control • High-pass filter: 40 Hz (12 dB/octave) • Low-pass filter: 16 kHz (12 dB/octave) • 2/3-octave spacing • Variable input level control • EQ bypass switch on both channels • Clip level indicators • Ground lift switch to disconnect signal ground from chassis ground

187,00 **224,00** EUR

STAGEDRIVE+ **



- PC Controllable Speaker Management System** • Configurable as a 3-way stereo crossover, 3, 4, 5 or 6-way mono crossover or distribution mixer with up to 6 outputs • Store 64 presets internally or 128 presets on a memory card • Remarkable 117dB S/N ratio via premium D/A conversion technology • Control via PC or via MIDI remote • Bessel, Butterworth and Linkwitz/Riley crossover filters

265,00 **318,00** EUR

MAC Power Amplifiers

MAC 2.2



2-CHANNEL 1500 WATT POWER AMPLIFIER

- 1500 Watts @ 4 Ω bridged mono • 2 x 750 Watts @ 2 Ω; 2 x 280 Watts @ 8 Ω • Convenient front-panel level controls
 High-visibility LEDs indicate clipping and protection • Switchable 30 Hz low-cut filter • Balanced 1/4" and XLR inputs
 • Speakon and binding post outputs • Low-noise variable speed fan • Compact two rack-space design

295,00 **354,00** EUR

MAC 2.3



2-CHANNEL 2200 WATT POWER AMPLIFIER

- 2200 Watts @ 4 Ω bridged mono • 2 x 1000 Watts @ 2 Ω; 2 x 340 Watts @ 8 Ω • Convenient front-panel level controls
 High-visibility LEDs indicate clipping and protection • Switchable 30 Hz low-cut filter • Balanced 1/4" and XLR inputs
 • Speakon and binding post outputs • Low-noise variable speed fan • Compact two rack-space design

338,00 **406,00** EUR

MAC 2.4



2-CHANNEL 3100 WATT POWER AMPLIFIER

- 3100 Watts @ 4 Ω bridged mono • 2 x 1800 Watts @ 2 Ω; 2 x 670 Watts @ 8 Ω • Convenient front-panel level controls
 High-visibility LEDs indicate clipping and protection • Switchable 30 Hz low-cut filter • Balanced 1/4" and XLR inputs
 • Speakon and binding post outputs • Low-noise variable speed fan • Compact two rack-space design

404,00 **485,00** EUR

Model

Description

STEALTH WIRELESS Systems

| | | | | |
|--|---|--|--------|-------------------|
| | Stealth Wireless | <p>STEREO WIRELESS SYSTEM FOR ACTIVE LOUDSPEAKERS</p> <ul style="list-style-type: none"> • Add wireless audio connectivity to any active loudspeaker • Enjoy faster setups and teardowns • Eliminate complex cable runs • Dual-channel transmitter (x1) with two XLR+1/4 • Single-channel receivers (x2) with one XLR output (per unit) • Replaces up to 200' of console-to-system cabling • No compromise in audio quality • Reliable UHF band; 16 selectable channels • Adjustable squelch eliminates interference • Grow your system using the Stealth Wireless Expander Pack* (sold separately) | 335,00 | 402,00 EUR |
| | Stealth Expander Kit | <p>2 ADDITIONAL STEALTH WIRELESS RECEIVERS</p> <ul style="list-style-type: none"> • Single-channel receivers (x2) with one XLR output (per unit) • Adds additional active loudspeakers to your Stealth Wireless System • Transmitter: (2) XLR+1/4 combo inputs • Receiver: (1) XLR output (per receiver) | 183,00 | 220,00 EUR |
| | NEW Stealth PRO Wireless | <p>Wireless Connection System for Active Loudspeakers</p> <ul style="list-style-type: none"> • Dual-channel UHF Transmission and True Diversity reception for mission critical applications • Auto frequency scan and sync between transmitter and receiver units • Two XLR + balanced TRS 1/4" combo inputs • Single XLR output sends the signal to powered speaker array a traditional amplifier-and-speaker combo • Aluminum and steel enclosures and removable antennae • Rack-mountable transmitter with optional front panel antenna placement • Backlit dual LCD displays with RF and AF metering • Trim size is easily 1U rack-mountable; two fit side-by-side in 19" rack • BNC extension cables included • Stealth Wireless Pro Expander Packs available | 527,00 | 632,00 EUR |
| | NEW Stealth PRO Expander Kit | <p>2 Additional Stealth Wireless Pro UHF Receivers</p> <ul style="list-style-type: none"> • Single-channel UHF receivers (x2) with one mini XLR output (per unit) Adds additional active loudspeakers to your Stealth Wireless Pro System | 352,00 | 422,00 EUR |

RADIUS Wireless Systems

| | | | | |
|--|---------------------------------|---|--------|-------------------|
| | RADIUS 100 NEW | <p>Professional UHF diversity wireless microphone system</p> <ul style="list-style-type: none"> • All-in-one, easy-to-use wireless microphone system for professional vocal applications • Dual-antenna UHF diversity receiver for increased reliability and signal consistency • UHF band operation (520 - 937.5MHz) • Receiver includes a high-visibility back-lit LCD display: Displays RF frequency and channel, AF and RF signal levels and other critical functions • Single-button scan feature for quickly identifying the optimal operating frequency • Sync function automatically synchronizes transmitter and receiver frequency • Squelch control for minimizing background noise during silent periods • Front-panel rotary volume control • Balanced XLR and unbalanced 1/4-inch mic or line-level outputs | | |
| | RADIUS 100 H | Set with Handheld Mic | 200,00 | 240,00 EUR |
| | RADIUS 100 L | Set with Lavalier Mic | 200,00 | 240,00 EUR |
| | RADIUS 100 HS | Set with Headset Mic | 200,00 | 240,00 EUR |
| | RADIUS 200 NEW | <p>Professional UHF True Diversity wireless microphone system</p> <ul style="list-style-type: none"> • All-in-one, easy-to-use wireless microphone system for the most demanding professional vocal applications • Dual-antenna/dual-receiver True Diversity design for mission-critical, dropout-free operation • UHF band operation (520 - 937.5MHz) • Receiver includes a high-visibility back-lit LCD display: Displays RF frequency and channel, AF and RF signal levels and other critical functions • Single-button scan feature for quickly identifying the optimal operating frequency • Sync function automatically synchronizes transmitter and receiver frequency • Squelch control for minimizing background noise during silent periods • Front-panel rotary volume control • Balanced XLR and unbalanced 1/4-inch mic or line-level outputs | | |
| | RADIUS 200 H | Set with Handheld Mic | 300,00 | 360,00 EUR |
| | RADIUS 200 L | Set with Lavalier Mic | 300,00 | 360,00 EUR |
| | RADIUS 200 HS | Set with Headset Mic | 300,00 | 360,00 EUR |